



中国比格科技发展(集团)有限公司

CHINA BIG S & T DEV(GROUP)CO.,LIMITED

Ms. Merlin

Email: meilingtu@china-big.com.cn

TEL: +86-23-67635049

FAX: +86-23-67635036

**Specification of 6480 Diesel 2WD SUV**



| Vehicle         |                          | NHQ6480D5                | NHQ6480G                 |
|-----------------|--------------------------|--------------------------|--------------------------|
| Size and weight | Overall dimensions (mm)  | 4771×1870×1828           | 4771×1870×1828           |
|                 | Wheel Base(mm)           | 2790                     | 2790                     |
|                 | Front wheel base (mm)    | 1580                     | 1580                     |
|                 | Rear wheel base (mm)     | 1580                     | 1580                     |
|                 | Curb mass (kg)           | 1900                     | 1820                     |
|                 | Gross vehicle weight(kg) | 2460                     | 2380                     |
|                 | Seating capacity         | 7                        | 7                        |
|                 | Tyre Size                | 245/70R17                | 245/70R17                |
| Power           | Fuel                     | <b>diesel</b>            | <b>Gasoline</b>          |
|                 | Engine                   | D19TCID2                 | 4G69S4N                  |
|                 | Emission                 | Euro IV                  | Euro IV                  |
|                 | Displacement (cc)        | 1850                     | 2378                     |
|                 | 60 KM Economy            | 5 (L/100KM)              | 7.5 (L/100KM)            |
|                 | Fuel supply              | Direct Injection         | EFI                      |
|                 | Max Power (kw/rpm)       | 100/4000                 | 100/5250                 |
|                 | Max Torque (N.m/rpm)     | 300/2800                 | 200/3000                 |
|                 | Compression ratio        | 16.5 :1                  | 9.8 :1                   |
|                 | Maximum speed (km/h)     | 160                      | 160                      |
| Transmission    | Transmission             | 5MT                      | 5MT                      |
| Chassis         | Approach angle (°)       | 28.6                     | 28.6                     |
|                 | Departure angle(°)       | 26.6                     | 26.6                     |
|                 | Brake                    | disc                     | disc                     |
|                 | Brake                    | disc                     | disc                     |
|                 | Suspension               | Independent Suspension   | Double Wishbone          |
|                 | Suspension               | Five-Link Suspension     | Five-Link Suspension     |
|                 | Minimum turning diameter | 12.4 m                   | 12.4 m                   |
|                 | Driving method           | 2WD                      | 2WD                      |
|                 | Steering                 | Hydraulic Power Steering | Hydraulic Power Steering |