

SHENZHEN CHINARY CO., LTD.

Rm.1804, Wensheng Center, Wenjin Plaza, 1010 Wenjin Road (N), Shenzhen 518020, China

E-mail: info@chinary.com.cn

Http://www.chinary.com.cn

Micro Steel Fibre

Type	Diameter (mm)	Length (mm)	Cross Section	Tensile Strength (MPa or N/mm ²)
MFH012001	0.12 ± 10%	1 ± 1	round	2400 min
MFH012003	0.12 ± 10%	3 ± 1		
MFH012006	0.12 ± 10%	6 ± 1		
MFH012010	0.12 ± 10%	10 ± 1.5		
MFH012016	0.12 ± 10%	16 ± 1.5		
MFH017001	0.17 ± 10%	1 ± 1		
MFH017003	0.17 ± 10%	3 ± 1		
MFH017006	0.17 ± 10%	6 ± 1		
MFH017013	0.17 ± 10%	13 ± 1.5		
MFH017175	0.17 ± 10%	17.5 ± 1.5		
MFH020006	0.20 ± 10%	6 ± 1		
MFH020010	0.20 ± 10%	10 ± 1.5		
MFH020014	0.20 ± 10%	14 ± 1.5		
MFH030125	0.30 ± 10%	12.5 ± 1.5		
MFH030020	0.30 ± 10%	20 ± 2		
MFH033125	0.33 ± 10%	12.5 ± 1.5		
MFH033020	0.33 ± 10%	20 ± 2		
MFH040125	0.40 ± 10%	12.5 ± 1.5		
MFH040020	0.40 ± 10%	20 ± 2		
MFH040025	0.40 ± 10%	25 ± 2.5		
Packing	in compound kraft paper bags with inner two in one film bags of 1/10/15/20/25Kg net each, 500/1000/1200Kg on pallets			
Remarks	1. Straight Micro Steel Fibre (Copper Coated Micro Steel Fibre) comply with ASTM A820 TYPE I standard. Parts comply with CE Certificate EN 14889-1 2. If you would have any special requirements for the specifications of Hooked-end Micro Steel Fibre, please kindly let us know it so as to meet thr demands			