Thermal POS printer series

Model: RP802

80mm thermal POS printer

Specification:

Printing Method	Thermal line printing
Printing Speed	250mm/s
Resolution	8mm/s,576 dots/line
Character Set	ANK character,GB18030(Chinese)
	Font A:12*24dots,
	Font B:9*17dots,
	Jan/traditional form:24*24dots
Barcode type	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/
	CODABAR/ITF/CODE39/CODE93/CODE128
Interface	USB+WLAN+serial
Power	DC 24V/2.5A
Cashbox control	DC 12V-24V/1A
Reliability（MCBF）	150km
Work environment	Temperature: 0~45ºC; Dampness:10~80%
Storage environment	Temperature: -10~60ºC; Dampness:10~90%
Paper Width	79.5± 0.5mm
Max diameter of paper roll	80mm
Paper thickness	0.06~0.08mm
Weight	1.3kg (N.W.) 2.80kg(G.W.)
Dimension	195Lx148Wx145H mm
Drivers:	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP
	/Win Vista/Windows 7/Linux/OPOS
Auto-cutter	All cut or partly cut as optional
Printing command	Compatible with POS/ESC command set
Line spacing	3.75mm(can be adjusted by command)

Feature

★ Variety of exterior casing color(red, beige,silver,ebony black,   computer white)

★ High speed、high life、high quality、low repair rate, apply to all sorts of business software

★ Increase lose sales avoiding function to avoid the situation of losing order, practically guarantee user's vital interests

★ All cut or partly cut as optional

★ Sopport download Logo printing

★ Standard GB18030 Chinese character

★ Support simplified & traditional Chinese, and multiple international language

★ 100MB Ethernet interface connection, print more quickly, avoid losing sales.

Application:

◆ Telecommunications

◆ Logistics

◆ Bank

◆ Market

◆ Monopoly store

◆ Catering

◆ Hotel

◆ Tax Administration

◆ Executive branch