


[Switching Adaptor](#)
[Linear Adaptor](#)
[DC-DC Converter](#)
[Car Adaptor](#)
[Transformer](#)
[AC-AC Converter](#)
[DC-AC Inverter](#)
[Open Frame](#)

SWITCHING ADAPTOR DESKTOP-INLET SOCKET 60 SERIES



ELECTRICAL SPECIFICATIONS

Input		Output	
Input Voltage Range	90-264V AC	Output Voltage	11 - 25.5V DC
Input Frequency	47-63Hz	Output Current	4.3A(60VA max)
Input Current	1.5A(max)	Output Tolerance	5%
		Ripple & Noise	1%p-p max
		Efficiency	>70%

GENERAL SPECIFICATIONS

Temperatures		Humidity	
Operating Temperatures	0 to +40°C	Operating Humidity	0 to 85% RH
Storage Temperatures	-10 to +60°C	Storage Humidity	1 to 90% RH
Hi-Pot Test		MTBF	
Hi-Pot	3000V AC	MTBF	50,000Hours at 25°C
EMISSION		SAFETY	
EMI/EMC	C-tick/FCC	Safety Approvals	UL/CUL/SAA/PSE/CE/CB
		Safety Compliant	UL 60950/EN 60950/AS/NZS 60950/IEC 60950

OUTPUT SPECIFICATIONS SERIES NO. : 3SI60

Plug Option


PART NO.	OUTPUT	
	VOLT	CURRENT (max)
3SI60-1104200	11.0V	4.20A
3SI60-1154200	11.5V	4.20A
3SI60-1204200	12.0V	4.20A
3SI60-1254080	12.5V	4.08A
3SI60-1303920	13.0V	3.92A
3SI60-1353700	13.5V	3.70A
3SI60-1404280	14.0V	4.28A
3SI60-1454130	14.5V	4.13A
3SI60-1504000	15.0V	4.00A
3SI60-1553870	15.5V	3.87A
3SI60-1603750	16.0V	3.75A
3SI60-1653630	16.5V	3.63A

PART NO.	OUTPUT	
	VOLT	CURRENT (max)
3SI60-1853240	18.5V	3.24A
3SI60-1903150	19.0V	3.15A
3SI60-1953070	19.5V	3.07A
3SI60-2003000	20.0V	3.00A
3SI60-2052920	20.5V	2.92A
3SI60-2102850	21.0V	2.85A
3SI60-2152790	21.5V	2.79A
3SI60-2202720	22.0V	2.72A
3SI60-2252660	22.5V	2.66A
3SI60-2302600	23.0V	2.60A
3SI60-2352550	23.5V	2.55A
3SI60-2402500	24.0V	2.50A

3SI60-1703520	17.0V	3.52A
3SI60-1753420	17.5V	3.42A
3SI60-1803330	18.0V	3.33A

3SI60-2452440	24.5V	2.44A
3SI60-2502400	25.0V	2.40A
3SI60-2552350	25.5V	2.35A

