


















Goldensun LED Panel Lights Catalog--1

Model	Power	Picture		Parameter	Color Temperature	Carton Measurement & PCS/CTN	
GT3030-9W	9W			Material : 6063A Aluminum IP44 Driver: AC85-265V Isolated Constant Current, 50/60Hz (A.PF>0.95 B.PF>0.5) Parameter: Ra≥80; A.Luminous Efficiency≥90lm/W ; B.Luminous Efficiency≥80lm/W Engineering Size : 295*295*10mm N.W : 0.84KG Integrating Size : 300*300*14mm N.W : 0.85KG A.Epistar LED Chip , Imported LGP B.Sanan LED Chip , Nano-composite LGP Viewing Angle: 120° Warranty : A.3 Years B.2 Years	3000K 4000K 6000K	67*35*33 cm	20pcs/ctn
GT3030-18W	18W			Material : 6063A Aluminum IP44 Driver: AC85-265V Isolated Constant Current, 50/60Hz (A.PF>0.95 B.PF>0.5) Parameter: Ra≥80; A. Luminous Efficiency ≥90lm/W ; B. Luminous Efficiency ≥80lm/W Engineering Size : 295*295*10mm N.W : 0.84KG Integrating Size : 300*300*14mm N.W : 0.85KG A.Epistar LED Chip , Imported LGP B.Sanan LED Chip , Nano-composite LGP Viewing Angle: 120° Warranty : A.3 Years B.2 Years	3000K 4000K 6000K	67*35*33 cm	20pcs/ctn
GT3060-24W	24W			Material : 6063A Aluminum IP44 Driver: AC85-265V Isolated Constant Current, 50/60Hz (A.PF>0.95 B.PF>0.5) Parameter: Ra≥80; A. Luminous Efficiency≥90lm/W ; B. Luminous Efficiency≥80lm/W Engineering Size : 295*595*10mm N.W : 1.68KG Integrating Size : 300*600*14mm N.W : 1.7KG A.Epistar LED Chip , Imported LGP B.Sanan LED Chip , Nano-composite LGP Viewing Angle: 120° Warranty : A. 3 Years B. 2 Years	3000K 4000K 6000K	67*35*33 cm	10pcs/ctn

GT6060-36W	36W			<p>Material : 6063A Aluminum IP44 Driver: AC85-265V Isolated Constant Current, 50/60Hz (A.PF>0.95 B.PF>0.5) Parameter: Ra≥80; A. Luminous Efficiency≥90lm/W ; B. Luminous Efficiency≥80lm/W Engineering Size : 595*595*10mm N.W : 2.75KG Integrating Size : 600*600*14mm N.W : 2.8KG A.Epistar LED Chip , Imported LGP B.Sanan LED Chip , Nano-composite LGP Viewing Angle: 120° Warranty : A. 3 Years B. 2 Years</p>	3000K 4000K 6000K	65*18*67 cm	5 pcs/ctn
GT30120-36W	36W			<p>Material : 6063A Aluminum IP44 Driver: AC85-265V Isolated Cosntant Current, 50/60Hz (A.PF>0.95 B.PF>0.5) Parameter: Ra≥80; A. Luminous Efficiency≥90lm/W ; B. Luminous Efficiency≥80lm/W Engineering Size : 295*1195*10mm N.W : 2.95KG Integrating Size : 300*1200*14mm N.W : 3.05KG A.Epistar LED Chip , Imported LGP B.Sanan LED Chip , Nano-composite LGP Viewing Angle: 120° Warranty : A. 3 Years B. 2 Years</p>	3000K 4000K 6000K	128*18*32.5 cm	5 pcs/ctn
GT6060-44W	44W			<p>Material : 6063A Aluminum IP44 Driver: AC85-265V Isolated Constant Current, 50/60Hz (A.PF>0.95 B.PF>0.5) Parameter: Ra≥80; A.Luminous Efficiency≥90lm/W ; B. Luminous Efficiency≥80lm/W Engineering Size : 595*595*10mm N.W : 2.75KG Integrating Size : 600*600*14mm N.W : 2.8KG A.Epistar LED Chip , Imported LGP B.Sanan LED Chip , Nano-composite LGP Viewing Angle: 120° Warranty : A. 3 Years B. 2 Years</p>	3000K 4000K 6000K	65*18*67 cm	5 pcs/ctn

GT6060-48W	48W			<p>Material : 6063A Aluminum IP44 Driver: AC85-265V Isolated Constant Current, 50/60Hz (A.PF>0.95 B.PF>0.5) Parameter: Ra≥80; A.Luminous Efficiency≥90lm/W ; B. Luminous Efficiency≥80lm/W Engineering Size : 595*595*10mm N.W : 2.75KG Integrating Size : 600*600*14mm N.W : 2.8KG A.Epistar LED Chip , Imported LGP B.Sanan LED Chip , Nano-composite LGP Viewing Angle: 120° Warranty : A. 3 Years B. 2 Years</p>	3000K 4000K 6000K	65*18*67 cm	5 pcs/ctn
GT30120-48W	48W			<p>Material : 6063A Aluminum IP44 Driver: AC85-265V Isolated Constant Current, 50/60Hz (A.PF>0.95 B.PF>0.5) Parameter: Ra≥80; A.Luminous Efficiency≥90lm/W ; B. Luminous Efficiency≥80lm/W Engineering Size : 295*1195*10mm N.W : 2.95KG Integrating Size : 300*1200*14mm N.W : 3.05KG A.Epistar LED Chip , Imported LGP B.Sanan LED Chip , Nano-composite LGP Viewing Angle: 120° Warranty : A. 3 Years B. 2 Years</p>	3000K 4000K 6000K	128*18*32.5 cm	5 pcs/ctn
GT60120-72W	72W			<p>Material : 6063A Aluminum IP44 Driver: AC85-265V Isolated Constant Current, 50/60Hz (A.PF>0.95 B.PF>0.5) Parameter: Ra≥80; A. Luminous Efficiency≥90lm/W ; B. Luminous Efficiency≥80lm/W Engineering Size : 595*1195*10mm N.W : 5.4KG Integrating Size : 600*1200*14mm N.W : 5.45KG A.Epistar LED Chip , Imported LGP B.Sanan LED Chip , Nano-composite LGP Viewing Angle: 120° Warranty : A. 3 Years B. 2 Years</p>	3000K 4000K 6000K	128*18*62.5 cm	5 pcs/ctn