

5.6"/6.4"/7"/8" Video

Small Video LCD Monitor

FEATURES

- Dual CH VIDEO/AUDIO In.
- Friendly OSD Function Controls.
- High Brightness , Wide-View Angle.
- True Color and High-Resolution.
- Accessories: 1. Bracket.
2. Power Adapter.
- Black Case (Option)



• CH-LCD56NDK-2D



• CH-LCD56DK-2D
• CH-LCD64DK



16:9
• CH-LCD70NDK-3
• CH-LCD70NDK-2D



• CH-LCD80AV-1

SPECIFICATIONS

| MODEL | CH-LCD56DK-2D | CH-LCD56NDK-2D | CH-LCD64DK | CH-LCD70NDK-3 | CH-LCD70NDK-2D | CH-LCD80AV-1 |
|------------------------|---|---|---|--|--|---|
| LCD Panel | 5.6" TFT LCD | | 6.4" TFT LCD | 7.0" TFT LCD | | 8.0" TFT LCD |
| Resolution | 640 x3 (RGB) x 480 | | 960 x 234 | 1440 x 234 (16:9) | 800 x3(RGB) x480 | 800 x 3(RGB)x600 |
| Brightness(nit) | 200(LED) | | 330 | 400(LED) | | 250/500(LED)(Option) |
| Contrast Ratio | 500:1 | | 350:1 | 400:1 | 500:1 | |
| Viewing Angle(U/D/L/R) | 50/70/70/70 | | 60/60/40/55 | 40/65/65/65 | 50/70/70/70 | |
| Operating System | NTSC/PAL Auto Switch | | | | | |
| Signal Input | 2CH A/V Input/ 1.0 Vp-p at 75Ω | | | | 2CH A/V Input/ 1.0 Vp-p at 75Ω/ PC: Analog R.G.B | |
| Audio Input | (MONO) 30 m~100 mVp-p | | | | | |
| Video/Audio Connector | Mini phone jack/Mini phone plug to RCA plug adapter | | | | | |
| Function Control | Mode ◀ ▶ Power OSD Control | | | | | |
| PC Connectors | 15 Pin "D" SUB/VGA/SVGA(Option) | | 2 x Mini Phone Jack | | 15 Pin "D" SUB(Option) | 15 Pin "D" SUB/VGA/SVGA |
| Panel Frame | Plastic | | | | | |
| Environment | Operating:[0°C~50°C]/Humidity:10%~85%(32°F~122°F) Storage:[20°C~60°C]/Humidity:10%~85%(-4°F~140°F) | | | | | |
| Power Supply | DC 12V 10%(DC 12-30V Option) | | | | | |
| Power Consumption | 3.6W | | 7.5W | 3.2W | 4.8W | 6W / 9.6W |
| Net Dimension(LxWxD) | 160 x 133 x 37mm (6.29 X 5.23 X 1.45Inch) | 150 x 127 x 28mm (5.90 X 4.99 X 1.10 Inch) | 172 x 144 x 37mm (6.77 X 5.66 X 1.45 Inch) | 179.6 x 120 x 23mm (7.07 X 4.72 X 0.9 Inch) | | 200 x 165 x 30mm (7.87 X 6.49 X 1.18 Inch) |
| Net Weight | 383g(0.844lbs) | 325g(0.916lbs) | 530g(1.16lbs) | 350g(0.771lbs) | | 523g(1.15lbs) |

☒ SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE