

产品型号 Item	额定电压 Rate Voltage (V)	额定电容 Rate Capacity (AH/10Hr)	端子 Terminal	规定尺寸/dimension(mm)				重量 Weight
				长/Leng th	宽/Widt h	高/Heigh t	总高/Total Height	
JS4-4	4V	4.0AH	T1	47	47	101	106	0.465KG
JS4-6	4V	6.0AH	T1	70	47	100	105	0.67KG
JS6-1.2	6V	1.2AH	T1	97	24	52	56	0.26KG
JS6-2.8	6V	2.8AH	T1	66	33	97	101	0.54KG
JS6-3.2	6V	3.2AH	T1	134	34	60	65	0.61KG
JS6-4	6V	4.0AH	T1	70	47	100	105	0.69KG
JS6-4.2	6V	4.2AH	T1	70	47	100	105	0.72KG
JS6-4.5	6V	4.5AH	T1	70	47	100	105	0.73KG
JS6-5	6V	5.0AH	T1	70	47	100	105	0.82KG
JS6-7	6V	7.0AH	T1	94	48	101	110	1.06kg
JS6-7.2	6V	7.2AH	T1	151	34	94	100	1.15KG
JS6-10	6V	10.0AH	T1 /T2	151	50	94	100	1.60KG
JS6-12	6V	12.0AH	T1 /T2	151	50	94	100	1.78KG
JS12-0.8	12V	0.8AH	引线	96	25	62	62	0.36KG
JS12-1.3	12V	1.3AH	T1	97	43	53	57	0.55KG
JS12-2.3	12V	2.4AH	T1	179	35	61.5	67	0.89KG
JS12-3.2	12V	3.2AH	T1	134.5	67	60	65	1.23KG
JS12-4	12V	4.0AH	T1 /T2	89	69	101	106	1.35KG
JS12-4.5	12V	4.5AH	T1 /T2	89	69	101	106	1.46KG
JS12-5	12V	5.0AH	T1 /T2	89	69	101	106	1.59KG
JS12-5.5	12V	5.5AH	T1 /T2	89	69	101	106	1.66KG
JS12-6	12V	6AH	T1 /T2	151	65	95	100	1.78KG
JS12-6.5	12V	6.5AH	T1 /T2	151	65	95	100	1.95KG
JS12-7	12V	7.0AH	T1 /T2	151	65	95	100	2.10KG
JS12-7.2	12V	7.2AH	T1 /T2	151	65	95	100	2.15KG
JS12-7.5	12V	7.5AH	T1 /T2	151	65	95	100	2.20KG
JS12-8	12V	8.0AH	T1 /T2	151	65	95	100	2.28KG
JS12-9	12V	9.0AH	T1 /T2	151	65	95	100	2.48KG
JS12-10	12V	10.0AH	T1/T2	151	98	95	99	3.15KG
JS12-12	12V	12.0AH	T1 /T2	151	98	95	100	3.45KG

JS12-13	12V	13.0AH	T1 /T2	151	98	95	100	3.65KG
JS12-14	12V	14.0AH	T2	151	98	95	100	4.00KG
JS12-16	12V	16.0AH	T3/T10	180	76	167	172	5.00KG
JS12-17	12V	17.0AH	T3/T10	180	76	167	172	5.20KG
JS12-20	12V	20.0AH	T3/T10	180	76	167	172	5.70KG
JS12-26	12V	26.0AH	T3 /T10	175	165	125	125	7.60KG
JS12-28	12V	28.0AH	T3	175	165	125	125	8.2KG