

Portable Bluetooth Thermal Printer Series

Model: DP-BM9000II

58mm portable thermal printer

Specifications:

Dimension(W x L x H)	74*104*45mm
Print method	Thermal Dot Line Printer
Paper width	57.5± 0.5mm
Print width	48mm
Weight (g)	250 (not including the paper roll)
Max diameter of paper roll	40mm
Dot per line	384 dots/line
Internal characters	ANK: 9x17,12x24; GBK: 24x24
Print speed	50~80mm/s
Life cycle time	50km(printing density under 12.5%)/100 million pulses
Text and graphic Support	English,figure,symbol,Chinese,graph,curve,icon pre-stored, barcode(CODE39/EAN13/EAN8/CODABAR/CODE128/CODE93/ITF), QR code, PDF417
Dot pitch (resolution)	203DPI/8 dots/mm
Interface	1) USB + serial + single bluetooth (android) 2) USB + serial + single bluetooth (ios) 3) USB + double bluetooth (android + ios)
Power	2000mAh 7.4V rechargeable Lithium battery
Recharge adapter	Stand by recharging / AC adapter
Self-check	Without paper /cover open
Black mark test	Supported
Paper feeding	Easy paper loading
Commands	ESC/POS compatible with order sets
Paper cut	By hands
Operate setting	Temperature: -10°C~50°C ; Humidity: 20%~85%
Recharge Setting	Temperature: 5°C~40°C; Humidity: 20%~85%
Storage Setting	Temperature: -20°C~70°C ; Humidity: 5%~95%
Standard accessories	Roll paper, AC adapter, li-ion battery,user manual
Optional accessories	Serial interface cable,USB cable, car charger,leather cover



Feature:

- ★ Portable device suited for outdoor usage
- ★ Black mark paper location sensor
- ★ Low battery indicator(7.4V,2000mAh)
- ★ Equipped with lithium battery for 4-8 hours continuous work
- ★ Various interface communication and interface capabilities
- ★ Bluetooth with high communication speed
- ★ Easy paper loading
- ★ High printing speed , up to 80mm/s.

Application:

- ◆ Mobile POS/Retail
- ◆ Hospitality
- ◆ Packing citation
- ◆ Deliveries
- ◆ Onboard Transportation
- ◆ Field reports/Installation
- ◆ Warehouse/logistics
- ◆ Utility billing/meter reading