

开启式单相空压机电机
Drip-proof Single-Phase Air-Compressor Motor

性能特点:

- 功率: 1HP-10HP
- 极数: 2P, 4P
- 机座: 56-215T
- 启动转矩: $T_{st} \geq 250\%$
- 防护形式: 开启式
- 防护等级: IP23
- 服务系数: 1.0, 1.15
- 均通过 CSA&CUS 安全认证
- 可接受手动保护器

Features:

- HP:1HP-10HP
- Pole:2P, 4P
- Frame: 56-215T
- Start Torque: $T_{st} \geq 250\%$
- Enclosure: ODP
- IP Class: IP23
- Service factor: 1.0,1.15
- CSA&CUS certified
- Accept Manual Thermal Protector

电机照片

HP	RPM 60HZ	NEMA FRAME	Model	Volts	HZ	ENCL.	S.F	Full Load AMPS	WGT. LBS.
1	3600	56	D56 1S2C	115/208-230	60	ODP	1.15	12/6.4-5.8	30
	1800	56	D56 1S4C	115/208-230	60	ODP	1.15	11.5/6.0-5.7	38
	1800	143T	D143T1S4C	115/208-230	60	ODP	1.15	11.5/6.0-5.7	41
1.5	3600	56	D56 1.5S2C	115/208-230	60	ODP	1.15	14.5/7.8-7.2	37
	1800	56	D56 1.5S4C	115/208-230	60	ODP	1.15	15.5/8.1-7.6	42
	1800	145T	D145T1.5S4C	115/208-230	60	ODP	1.15	15.5/8.1-7.6	45
	3600	145T	D145T1.5S2C	115/208-230	60	ODP	1.15	14.5/8.0-7.6	41
2	3600	56	D56 2S2C	115/208-230	60	ODP	1.15	18/10.1-9.2	44
	1800	56	D56 2S4C	115/208-230	60	ODP	1.15	19.0/10-9.3	47
	1800	145T	D145T2S4C	115/208-230	60	ODP	1.15	19.0/10-9.3	50
	3600	145T	D145T2S2C	115/208-230	60	ODP	1.15	18/10.2-9.4	48
3	3600	56	D56 3S2C	115/208-230	60	ODP	1.15	25/14.2-13	60
	3600	145T	D145T3S2C	115/208-230	60	ODP	1.15	25/14.2-13	67
	1800	182T	D182T3S4A	208-230/460	60	ODP	1.15	13.5-12/6.2	88
5	3600	184T	D184T5S2A	208-230/460	60	ODP	1.15	22-20/10	95
	1800	184T	D184T5S4A	208-230/460	60	ODP	1.15	22.5-20/10	96
6	3600	56	D566S2A	230	60	ODP	1.0	22.8	56
7.5	1800	213T	D213T7.5S4A	208-230/460	60	ODP	1.15	32.8-30/15.2	140
10	1800	215T	D215T10S4A	208-230/460	60	ODP	1.0	41.2-39/19.5	153