

## Model 6106 Coach (10.44m Diesel)



### 外形参数 Size

总长/总宽/总高Length/Width/Height (mm) 10440\*2490\*3540

内高 Interior Hight (mm) 2000

### 发动机 Engine

发动机型号 Engine model 玉柴欧三排放柴油机，型号：YC6L280-30（Euro 3）

YUCHAI diesel engine YC6L280-30 (Euro 3)

发动机型式 Engine type 后置，直列六缸四冲程、增压中冷、水冷、电控直喷

Rear mounted, 6 cylinders in-line, 4 stroke, turbo-charged, water cooled, electrical control direct injection

排量 Displacement (L) 8.4

最大功率/转速  
Max.power/rotating speed (kw/rpm) 206/2200

最大扭矩/转速  
Max. torque/rotating speed (kw/rpm) 1100/1200-1400

### 性能参数 Performance

底盘型号 Chassis model /

最高车速 Top speed (km/h)	120
轴距 Axle distance (mm)	4930
前悬/后悬 Front / Rear Overhang (mm)	2350 / 3160
接近角/离去角 Angle of Approach / Departure (°)	9.3/9.9
轮距 (前/后) Wheel Trach (Front / Rear) (mm)	1922 / 1838
制动距离 (时速30KM满载状态下)	<10m
Brake Distance (V=30km/h fully loaded)	
油箱容积 Fuel Tank (L)	220
油耗 (L/100km) (限定工况下)	≤22
Fuel consumption (on certain condition)	
总质量/整备质量 (kg) Curb weight	13500/9800
<b>基本配置 Basic Specification</b>	
离合器 Clutch	单片、干式、膜片式、直径430mm
	Single, dry, diaphragm type, diameter is 430mm
变速器 Transmission	5档手动带同步器、型号: QJ1205
	Domestic 5 forwards manual with synchronizer, model: QJ1205
后桥 Rear axle	单级减速, 整体式桥壳, 速比: 4.11
	Single reduction final drive, integral axle housing, speed ratio: 4.11
前桥 Front axle	拳端式工字梁结构 Ends fist, I section
悬架系统 Suspension system	空气悬挂, 前2后4 Air suspension, Front 2/ rear 4
转向系统 Steering system	整体式动力转向 Integral power steering
制动系统 Braking system	双管路气制动、干燥器、储能弹簧气室、WABCO ABS 带刹车间隙自动调整臂、电涡流缓速器
	Dual circuit air brake, drier, energy storage spring chamber, WABCO ABS + automatic backlash adjustment arm, electrical wave absorber
轮胎Tire	规格: 10R22.5, 有备胎 Specification: 10R22.5, with spare tire

功能配置 Functional Specification	
车身类型 Body type	SS400和16Mn矩型钢管焊接成型骨架，全承载车身，汽车专用双面镀锌板涨拉蒙皮，全车保温隔热处理，底部防腐处理，四级踏步
	The body of bus is welded by SS400 and 16Mn rectangular steel tube, Monocoque structure body, side panels are stretched high-quality galvanized panels. The bottom of the chassis is specially treated with anti-corrosion glue. The whole bus is heat insulation, four steps.
内饰 Interior trim	空调内饰，带读书灯和空调出风口式双面内行李架，豪华换气扇式安全顶窗，电动除霜倒车镜，凹地板铺装地板革
	Air conditioner interior trim, double face interior luggage rack with reading lamps and A/C ventilators, luxury air change fan type safety ceiling window, electric defroster rearview mirror, concaved floor with vinyl.
车门及门泵 Door and door pump	1个外摆乘客门 outward swinging passenger door
车窗 Window	全封闭式钢化玻璃（两侧后窗为活式），全车豪华折叠式窗帘，推拉式司机窗
	Full-closed hardened glass (rear side windows are active), luxury foldable curtain, pull-push driver window
空调系统 A/C system	非独立顶置空调，主要部件如压缩机等为进口，制冷量24KW
	Dependent ceiling air conditioner, the main component such as compressor are imported, and the refrigerating output is 24KW
暖风系统 Heating system	大功率除霜器 High-power defroster
座椅及附件 Seat and accessories	47+1 座（带导游座椅），2+2高靠、背可调式航空座椅，带网袋、把手、扶手、侧拉、座号牌、全车安全带、脚踏
	47+1 seats (with tour guide seat), 2+2 airline high-back adjustable seats, with bag, handle, armrest, side pull, seat mark, safety belts, foot pedal
视听系统 Video and Audio	硬盘播放器+ 一台17寸液晶显示器+ 一台15寸液晶显示器 Hard disk player + 17" LCD monitor + 15" LCD monitor
灯具 Lamp	组合前照灯，前顶示高灯，车身侧标志灯，高位刹车灯
	Integral front lamp, front ceiling height lamp, side mark lamp, high-level brake lamp
服务设施 Service equipment	电子钟，发动机仓自动灭火器，8KG灭火器，工具箱，四个安全锤
	E-clock, engine compartment automatic fire distinguisher, 8KG fire extinguisher, vehicle tools, 4 safety hammers
其他 Others	倒车监视器 rear view monitor