Machine		BGA Rework Station					IR PREHEATING PLATER		Electronic Hot Plate
Model		T-862	T-862++	T-870A	T-890	T-835	T-8280	T-8120	T-946
		Puhui (€	pyhyi (€	PANA	Puhui	Puhui CE	pyhyi (E	pyhui (E	bhihi CE
Power Voltage		AC220V/110V 50-60Hz	AC220V/110V 50-60Hz	AC220V/110V 50-60Hz	AC220V/110V 50-60Hz	AC220V/110V 50-60Hz	AC220V/110V 50-60Hz	AC220V/110V 50-60Hz	AC220V/110V 50-60Hz
Mode Of Heating		Infrared heating	Infrared heating	Infrared heating	Infrared heating	Infrared heating	Infrared component heating	Infrared component heating	Timing mode and Sustained mode
Power	Total Power	600W	800W	1000W/220V 1200W/110V	1500W	300W	1600W	800W	800W
	Preheater	350W	450W	800W/220V 1000W/110V	1200W		1500W	600W	800W
	Infrared lamp	100W	100W	150W	300W	100W			
Temperatur e	Preheater	60−200℃	60−200℃	60−200℃	0-350℃		0−450℃	0−450°C	0−450℃
	Infrared lamp	100−350℃	100−350℃	200−450℃	8 Intelligent temperature waves heating	0−350℃			0-999S Time adjustable
	936 soldering	200−450℃	200−450℃						
Working bench parameters	Working	350*260mm	360x270mm	360X240mm	320X330mm		410x316mm	120x120mm	180X240mm
	Preheating	120X80mm	120X120mm	240X180mm	245X260mm		280X270mm	200X240mm	180X240mm
	Infrared lamp	⊄ 28mm	⊄28mm, ⊄ 38mm, ⊄48mm	⊄ 70mm	70X70mm	⊄ 35mm			
	Chips size	15X15-25X25mm	15X15-35X35mm	35-50mm	60X60mm	15X15- 35X35mm			
Package	Package size	460X340X305mm	460X340X305mm	430X260X420mm	316X410X290mm	290X170X300m m	400X200X510 mm	300X270X150m m	300X210X250mm
	Weight	8Kgs	8Kgs	11Kgs	11Kgs	3.5Kgs	7Kgs	3.5Kgs	6.5Kgs