

DIN764 LINK CHAIN

DIA.		I.L.		I.W.	O.W.	LENGTH PER 11 LINKS		WT/100 M	TEST LOAD	BREADING ROAD
MM	±MM	MM	±MM	MM	±MM	MM	±MM	KG	KG	KN
4	0.20	16	0.30	5.0	14	176	1.60	31.30	7.0	400
			0.20				0.90			
5	0.20	18	0.40	7.0	18.2	198	1.80	51.40	11.8	680
			0.20				1.00			
6	0.20	21	0.50	8.0	21.5	231	2.00	74.00	16.5	850
			0.20				1.10			
8	0.20	28	0.50	11.0	29	308	2.20	131.50	32.0	1680
			0.30				1.20			
10	0.30	35	0.60	14.0	36	385	2.70	200.00	50.0	2630
			0.30				1.50			
12	0.30	42	0.60	16.0	41	462	3.20	298.00	70.0	3680
			0.30				1.80			
13	0.40	45	0.70	18.0	47	495	3.50	350.00	80.0	4200
			0.40				2.00			
14	0.45	49	0.75	20.0	48	539	3.80	406.00	92.0	4830
			0.45				2.00			
16	0.50	56	0.90	22.0	58	616	4.30	520.00	125.0	6700
			0.50				2.50			
18	0.80	63	1.00	24.0	65	693	4.70	650.00	160.0	8400
			0.50				2.80			
20	1.00	70	1.10	27.0	72	770	5.40	820.00	200.0	10000
			0.60				3.20			
23	1.20	80	1.30	31.0	83	880	6.20	1100.00	250.0	13000
			0.70				3.50			
26	1.30	91	1.50	35.0	94	1001	7.00	1400.00	320.0	16000
			0.80				4.00			
28	1.40	98	1.60	36.0	101	1078	7.50	1650.00	360.0	18000
			0.90				4.30			
30	1.50	105	1.70	39.0	108	1156	7.80	1900.00	415.0	20750
			0.90				4.60			
33	1.70	115	1.90	43.0	119	1265	8.50	2250.00	500.0	25000
			1.00				4.90			