



Easy Storage Technologies Co., Ltd.

5/F, South Wing, Building 23#, Road Kezhixi, Science&Technology Industrial Park,
Nanshan, Shenzhen, China, 518057

Tel: +86-755-26503848

Fax: +86-755-26613808

Contact Person: Anzer Fang

Email: afang@szest.com

Skype: easystorage7

Website: www.szest.com

SPECIFICATION

	ITEM	SDVR001	SDVR002	SDVR004
VIDEO	VIDEO INPUT	1 channel	2 channels	4 channels
	VIDEO OUTPUT	1 channel, 1.0V, p-p, 75Ω, BNC		
	VIDEO FORMAT	Support PAL/NTSC		
	VIDEO COMPRESSION	H.264 High Profile		
	RECORD RESOLUTION	720x576(PAL)/ 720x480(NTSC)	1280x512(PAL)/ 1248x416(NTSC)	1280x1024(PAL)/ 1248x832(NTSC)
	FRAME RATE	25fps(D1 PAL) 30fps(D1 NTSC)	50fps(D1 PAL) 60fps(D1 NTSC)	100fps(D1 PAL) 120fps(D1 NTSC)
	VIDEO BITRATE	660Kbps ~ 1.5Mbps, 4 level video quality	1.32Mbps ~ 3Mbps, 4 level video quality	1.98Mbps ~ 4.5Mbps, 4 level video quality
AUDIO	AUDIO INPUT	1 channel	2 channels	4 channels
	AUDIO INPUT FORMAT	20KΩ, RCA		
	AUDIO OUTPUT	1 channel, 500Ω, RCA		
	AUDIO LEVEL	1V ~2V, p-p		
	AUDIO COMPRESSION	G.711		
STORAGE	STORAGE	SD card, external USB device (memory stick or hard drive)		
	FILE FORMAT	AVI		
INTERFACE	SENSORS	1 speed sensor, 1 ignition sensor, 3 sensors for brake, return etc.		
	COM PORT	2 RS232 port, 1 RS485 port		
	NETWORK	RJ45, 10M/100M Ethernet		
	GPS	Support GPS receiver(optional), can record GPS information along with video and audio. GPS data format: NEMA0183, Baudrate: 4800bps		
SOFTWARE	PLAYER	Specially designed player for the DVR		
	THIRD PARTY SOFTWARE	Windows Media Player(Ver 11.0 or above), VLC Media Player(Ver1.0.0 or above)		
POWER	INPUT POWER	From +8VDC to +32VDC		
	POWER OUTPUT	DC, +12V@1.5A, +5V@1A		
	POWER COMSUMPTION	Working power: <5W, Strand by power: 0.1W ((exclude camera, SD card, monitor)		
OTHER	WORKING TEMPRETURE	From -30 Celsius degree ~ +60 Celsius degree		
	SIZE	12cm X 9cm X 2cm (4.75" x 3.5" x 0.8")		
	WEIGHT	0.3KGS		
	PACKAGE SIZE AND WEIGHT	21cm X 14cm X 7.5cm (8.3"x 5.5"x 3.0"), 0.63KG		