

# Xiamen Dlight Star Technology Co.,Ltd.



Address: NO.358 Jiqu Road Tong'an Industry District, Xiamen, Fujian, China

Tel: 86-592-7107075 Fax: 86-592-7107075 Mobile: 86-13779971206

Email: a.lee@dlightstar.com, website: www.dlightstar.com

Skype: amyli8512

## Automotive Rechargeable LED Working light series

| PRODUCT IMAGE                                                                       | ITEM NO.   | DESCRIPTION & SPECIFICATIONS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | PACKAGING                                                      | packing information                                                                                                                                                       |
|-------------------------------------------------------------------------------------|------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|    | DL306S-IV  | <p><b>Light Source:</b><br/>front (working light): 12*0.5W SMD 2835 LED<br/>Top light: 1*3W led<br/>Warning light : red &amp; blue led</p> <p><b>Light Output:</b><br/>450LM for working light<br/>120lm for Top light</p> <p><b>Mode Dimmer:</b><br/>work light(front)-flashlight(top)-off<br/>work light dimmer (70%-50%-100%)<br/>warning lights are hided(hold on 1.5s)</p> <p><b>Runtime:</b><br/>3.8hrs for working light<br/>10hrs for flashlight<br/>50 hrs for red &amp; blue warning light</p> <p><b>Power type:</b> 2* x 18650 (4400mAh/3.7V)</p>                                                                                                                                                                                                                                                                                                                     | Color box packing                                              | <p>Inner packing: White box/color boxes<br/>Packing Size: 37.5x12.5x8<br/>Weight: 0.7kg/set<br/>Carton size: 52x38.5x42<br/>Q'ty/Ctn: 20pcs/ctn<br/>GW./NW. 15kg/14kg</p> |
|   | DL306S-111 | <p><b>Light Source:</b><br/>front (working light): 30*SMD 3014<br/>Top light: 1*1W led<br/>back (Red flash light) 1* 0.5W Led</p> <p><b>Light Output:</b><br/>365LM for working light(2000lux at 50cm)<br/>50lm for Top light</p> <p><b>Mode Dimmer:</b><br/>work light(front)-flashlight(top)-red light(back)<br/>work light dimmer (80%-50%-100%)<br/>back red light can be hided(hold on 1.5s)</p> <p><b>Runtime:</b><br/>3.5hrs for working light<br/>16hrs for flashlight<br/>48hrs for red light</p> <p><b>Power type:</b> Rechargeable 18650 (2400mAh/3.7V)</p> <p><b>Materials:</b> PC+TPR<br/><b>Dimension:</b> 264 x62x45mm.</p>                                                                                                                                                                                                                                       | Color box packing                                              | <p>Inner packing: White box/color boxes<br/>Packing Size: 37.5x12.5x8<br/>Weight: 0.7kg/set<br/>Carton size: 52x38.5x42<br/>Q'ty/Ctn: 20pcs/ctn<br/>GW./NW. 15kg/14kg</p> |
|  | DL203V1    | <p><b>Light Source:</b><br/>front (working light): 6*SMD 2835<br/>warning light: 1*1W SMD 3030 red led &amp; Blue led<br/>back (Red flash light) 1* 0.5W Led</p> <p><b>Light Output:</b><br/>220LM for working light(2000lux at 50cm)<br/>35lm for red light<br/>25lm for blue light</p> <p><b>Mode Dimmer:</b><br/>work light dimmer (100%-50%)<br/>Warning light -SOS (can be hided)(hold on 1.5s)</p> <p><b>Runtime:</b><br/>4hrs for working light<br/>25hrs for Warning light<br/>42 hrs for SOS</p> <p><b>Recharge time:</b> 3hrs</p> <p><b>Power type:</b> Rechargeable 1500mAh/3.7V</p> <p><b>Materials:</b> PC+ABS<br/><b>Dimension:</b> 110 x74.4x28mm<br/><b>Weight:</b><br/>* Over Angle 100 ° of working light illumination, color temperature can be customized from 2700-8000 k, more than 80 ra coloration.<br/>*The lamp body can adjust rotate 360 degrees</p> | clamshell+ color box packing<br><br>light+0.5m USB charge line | <p>Inner packing: color box packing<br/>Packing Size: 15x10x4 CM<br/>Weight: 0.2kg<br/>Carton size: 45x40x20cm<br/>Q'ty/Ctn: 60pcs/carton<br/>GW./NW.: 12.5KG/12KG</p>    |

|                                                                                     |                                                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                                |                                                                                                                                                                    |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|     | <p><b>Model:DL-H510R</b></p> <p><b>on the stage of mold opening</b></p> | <p><b>Light Source</b><br/>front (working light): 10*SMD 2835<br/>Flashlight: 1*3W CREE XPE-R3</p> <p><b>Light Output</b><br/>385LM for working light<br/>180lm for Flashlight</p> <p><b>Mode Dimmer</b><br/>work light(front)-100% on-50% on-off (1.5s hold on )flashlight 100% on- 50%on -off</p> <p><b>Red and blue light visible power indicate</b></p> <p><b>Charge indicate</b><br/>red light flash means charging.<br/>blue A/B/C all light on means power full.</p> <p><b>Runtime</b><br/>3.5hrs for working light<br/>4hrs for flashlight</p> <p><b>IP Grade:IPx4</b></p> <p><b>Power type:</b> Li-polymer battery (2400mAh/3.7V)</p> <p><b>Shock resistant:</b> 1.5m highth drop still work well</p> <p><b>Magnetic:</b> yes</p> <p><b>1. Over Angle 100 ° of working light illumination, color temperature can be customized from 2700-8000 k, more than 80 ra coloration.</b></p> <p><b>2. Specification can be customized according to client's request.</b></p> | <p><b>clamshell packing</b></p> <p><b>Pen light + 0.5m USB Charge line</b></p> | <p>Inner packing:clamshell packing<br/>Packing Size: 35x12.5x3 CM<br/>Weight: 0.3kg<br/>Carton size:36x26x31cm<br/>Q'ty/Ctn:20pcs/carton<br/>GW./NW.:6.5KG/6KG</p> |
|    | <p>DL1501w</p>                                                          | <p><b>Product name:</b> working light</p> <p><b>Model:</b> DL1501W</p> <p><b>Material:</b> ABS</p> <p><b>LED type:</b> 3W COB+1W F8</p> <p><b>Light modes:</b> on- 1 LED (top)- off- COB- off</p> <p><b>Battery type:</b> 3*AA</p> <p><b>Item size:</b> 57*215mm</p> <p><b>Weight:</b> 157.3g</p> <p><b>LED brightness:</b> 80LM</p> <p><b>Body color:</b> Orange,red and green (customized according to your demand )</p> <p><b>Certification:</b> CE, RoHS, FCC</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | <p><b>Color box/white box</b></p>                                              |                                                                                                                                                                    |
|  | <p>DL152</p>                                                            | <p><b>Light source:</b> front (working light): COB 3W</p> <p><b>Top light:</b> 5*1W LED</p> <p><b>Light output:</b> 190lm for working light</p> <p><b>Power type:</b>Rechargeable 18650 (2400mAh/3.7V)</p> <p>The body can be folded free around 90°</p> <p><b>Rotation hook:</b>360°</p> <p><b>charging time:</b> 6-7 hours</p> <p><b>working time:</b> 6 hours</p> <p><b>service life:</b> Up to 8-100000 hours</p> <p><b>There are some strong magnetics on the back and the bottom of the body.</b></p> <p><b>Double hook available</b></p>                                                                                                                                                                                                                                                                                                                                                                                                                               | <p><b>Color box/white box</b></p>                                              |                                                                                                                                                                    |