



# LTC-S600 Dual SDI Eptz HD Camera



## Advantages Features

- ※ Adopt the highest industrial level DSP technology, use 1/1.7 inch 12MP high quality sensor, capture 3840x2160 ultra high definition image, 2 streams of 1080P full HD video output simultaneously: one stream output panoramic image; another stream output close-up shot image
- ※ Smart & Solid design
- ※ Dual SDI output
- ※ Standard VISCA control

- ※ Can select different ultra HD lens:(such as 5mm,8mm,12mm or other lens)
- ※ 1920 x 1080p30 full HD resolution
- ※ 72° FOV
- ※ RS232/485 Control
- ※ WDR, 3D Noise Reduction feature
- ※ Mounts: Wall mount & in-ceiling mount available

## Technical Specification

|                             |  |
|-----------------------------|--|
| <b>Model No.</b>            | <b>LTC-S600</b>  |
| <b>Sensor</b>               | 1/1.7 inch high quality, 12MP SONY CMOS Sensor                     |
| <b>Video System</b>         | 1080p30/25   |
| <b>Optical Lens</b>         | 5mm - 13.6mm optional  |
| <b>H. FOV</b>               | 5mm lens: -72°(Far)<br>7.8mm lens: 57°(Far)<br>12mm lens: 47°(Far) |
| <b>Control Port</b>         | RS232/RS485  |
| <b>Video Port</b>           | Dual SDI ports   |
| <b>SNR</b>                  | More than 50dB   |
| <b>Focal Length</b>         | f=3.6(wide) - 13.6mm(tele)   |
| <b>Minimum Lux</b>          | 0.1Lux   |
| <b>White Balance</b>        | Auto/Manual  |
| <b>Focus</b>                | Auto/Manual  |
| <b>Iris</b>                 | Auto/Manual  |
| <b>Electronic Shutter</b>   | Auto/Manual  |
| <b>BLC</b>                  | Auto/Manual  |
| <b>Input Voltage</b>        | DC12V  |
| <b>Dimension(W x H x W)</b> | 148mm x 132mm x 161mm  |
| <b>Net Weight</b>           | 0.9KG(2LBS)  |

\*\*\*Product specification are subject to change without notice\*\*\*