

(L611) 4G LTE Router



SELLING KEY

Appearance: Smart and Portable, With Stylish Appearance

Battery: Inbuilt 2000mAH Removable Li-Battery, Samsung battery available also

Chipset: Qualcomm MDM9215

Rate: DL 100Mbps, UL 50Mbps

Network: L611 is with 5 modes and 9 bands, customize FDD/TDD bands

Customize: Do OEM for MOQ1000pcs. Customize Logo, Software

OEM: We do OEM For China Mobile, China Unicom, China Telecom Already

Specifications

Hardware Info		
Processor	Qualcomm 28nm MDM9215	
TD-LTE	3GPP/3GPP2 Release9, Category 3, up to 68M DL and 17M bps UL@20MHz bandwidth	
FDD LTE	3GPP/3GPP2 Release9, Category3, up to 100M DL and 50M bps UL@20MHz bandwidth	
TD-HSPA+	3GPP/3GPP2 Release7, up to 4.2Mbps DL and 2.2Mbps UL	
DC-HSPA+	3GPP/3GPP2 Release8, up to 42Mbps ,category 24, 5.76M bps UL	
HSPA+	3GPP/3GPP2 Release7, up to 14.4Mbps ,category 10, 5.76M bps UL	
HSPA	3GPP/3GPP2 Release6, up to 7.2M bps DL,category 7/8, 5.76M bps UL	
UMTS	3GPP Release4, up to 384 Kbps DL and UL	
EDGE	3GPP Release4, Multislot class 12, up to 237 Kbps	
GPRS	3GPP Release4, Multislot class 10, up to 85.6Kbps	
Frequency	LTE TDD : 1.9(B39) / 2.3(B40) / 2.6(B38) GHz / 2.6(B41) GHz	Frequency Customizable
	LTE FDD : 1800(B3) / 2100(B1) / 2600(B7) MHz	
	TD-SCDMA: 2.0(B34) / 1.9(B39) GHz	
	UMTS: B1(2100MHz) / B2(1900MHz) / B5(850MHz) / B8(900MHz)	
	GSM: B2(1900MHz) / B3(1800MHz) / B5(850MHz) / B8(900MHz)	
Peak rate	LTE FDD : DL/UL 100 / 50 Mbps (Category 3)	
LCD	1.4 inch	TFT
Button	1 Power	
T-Flash card	Up to 32 GB	
WIFI	802.11 b/g/n	2*2 MIMO
Battery	2000mAh Lion	6 hours working time 250 hours standing time
Port	1 * MicroUSB 1 * Standard USIM 1 * MicroSD	
Antenna	External/Internal	MIMO Supported

Charger	Output : 5V DC±10%; Output : 1.5A~1.8A; Input : 100V~240V,50Hz~60Hz	
Working Temperature	-10°C to 45°C	
Working Humidity	5% - 65%	
Storage Temperature	-30°C to 80°C	
Storage Humidity	5% to 95%	
Software Info		
OS	Win7, Windows XP, Vista, Mac OS	
Language	Chinese & English	Multi Languages supported
Sharing	Up to 10 sharings	
Settings		
SMS	Supported	
Contact Book	Supported	
APN Setting	Supported	
WIFI Settings	Supported	
Device Settings	Supported	
Routing Settings	Supported	
Firewall Settings	Supported	
Certification		
	CE Granted	Up to customer
Else		
Size	96mm * 59mm * 14mm	For reference, to be decided
Weight	105g	
Standby Time	Up to 250 Hours	Finally decided by Battery
Working Time	Up to 6 Hours	Finally decided by Battery