

Handling capacity (t/h)	2~4	4~6	5~10	6~12	7~13	8~15
Driving Motor Power (kw)	3.0+0.55	4.0+0.75	5.5+1.1	7.5+1.5	11+2.2	11+3.0
Weight kg	1000	1400	1800	2200	2400	2600
Outer Size (L×W×H) mm	1885x1450x1150	2980x1883x1210	2980x2033x1210	2980x2233x1210	2980x2433x1210	2980x2633x1210

Applications:

1. Electronic waste disposal (refrigerator dismantling line)
2. Separation of aluminum cans and ferrous metals
3. Separate non-ferrous metals from the bottom ash of boiler
4. Separate aluminum or copper block from the sections of abandoned cars
5. Separate non-ferrous metals from the glass scrap
6. Separate non-ferrous metal impurities in some production lines(such as plastic recycling production line)
7. Separate non-ferrous metals from recycled plastic doors and windows
8. Separate non-ferrous metals from the wood

Advantages:

1. Rich experience in design and production can ensure mature product technology, stable performance and reliable quality

2. Mass production, mature technology, stable quality
3. Simple structure, easy and convenient to install, operate and maintain
4. Complete secure facilities, full functions
5. Beautiful appearance, retainer plates and door panels are stainless steel wiredrawing board, high-grade lock

For more detail info, please feel free to visit our website www.magnetonmove.com or inquire us at mag@e-magnet.cn at any of your convenience.