



SHENZHEN KINGSAKO ELECTRONICS CO., LTD

5-6F, C Building, He-Xi, Huanggangling Industrial, Xixiang, Baoan, Shenzhen, CHINA

Tel: 0086-755-61153288 mail:szsako@sako.com.cn skype:szsakopower Web: www.kingsako.com

SAKO PCS 110V Series OFFLINE UPS



SAKO PCS 110V Series MAIN FUNCTION

- Automatic Voltage Regulation (AVR)
- Wide Input Voltage Range Option
- High/Low Voltage Protection
- Over Load / Short Protection
- Cool Start Computer Even There Is No Main Power
- Automatic Restart
- Automatic Recharge Even UPS Is Off
- Beeping Alarm
- Colored LED Display
- Intelligent Battery Management
- Smart RJ11 & USB Option
- Compatibility With Generators



OHSMS 28001 ISO 9001:2000 ISO 14001:2004



SAKO PCS 110V Series TECHNICAL PARAMETER

Product	Requirements	Model 1	Model 2
Power (VA)		PCS-700	PCS-1300
Input	Voltage (VAC)	80-145VAC & 180-275VAC ± 5V	
	Frequency (Hz)	60Hz ± 10%	
Output	Voltage (Inverter Mode)	115VAC ± 10%	
	Capacity (W)	1 Computer	2 Computers
	Frequency (Inverter Mode)	60 ± 2.5Hz	
	Transfer Time (ms)	≤10ms Typical	
	Waveform	Modified-Sinewave	
Protection	Spike & Surge Suppression	Yes	
	Over/Under Voltage	Switch To Bat. O/P When Mains Over Regulation Range	
	Over Load /Short Circuit	Fuse & Current Limited For Both Mains And Battery Modes	
Function	Cool Start	Cool Start Computer Even There Is No Main Power	
	Automatic Recharge	Automatic Charge When UPS Is Off	
Battery	Type	Lead-Acid Miantenance-Free	
	DC Bus	12V7.0Ah	12V7.0Ah
	Number	1 PC	2 PCS
	Recharge Time	8 Hours ≥ 90%	
	Back Up Time(One PC)	10-15mins	10-15mins
Physical	Weight (KGs)	6.5	11
	Shipping Wt. (KGs)	7	11.5
	Product Dimensions (mm)	335*95*160 mm	355*120*195 mm
	Packing Dimensions (mm)	395*360*230 mm/ 2 PCS in 1 Carton	435*395*275/ 2 PCS in 1 Carton
Soft ware	Windows & NT	Auto Save & Shut Down	
Efficiency	AC-AC	1	
	DC-AC	0.6	
Acoustic	Noise Level (dB)	≤ 45 dB	
Environmental	Temperature	-5°C ~ 45°C Degree	
	Humidity	20% to 90%	
Power Outlets	No. And Types	4 SOCKETS	