

CDSD系列标准型半电动堆垛车

CDSD SERIES STANDARD TYPE SEMI-ELECTRIC STACKER

主要特点

MAIN CHARACTER

1. 选用进口液压站，低噪音，小振动，密封性能好，确保起升下降平稳可靠
2. 结构轻巧，特殊压制工艺制造的“C”型钢门架，坚固耐用，使用寿命长
3. 配置免维护蓄电池，电量持久，并选用智能充电器，德国REMA充电插件，充电方便快捷
4. 可调货叉可定制，可调范围340~830mm

1. WINNER hydraulic power pack, low noise, few vibration and excellent leak tightness, ensures smooth lifting
2. High-strength frame design and "C" shaped mast, strong and durable, ensures longer service life
3. Maintenance-free battery, intelligent charger, REMA plug from Germany
4. Adjustable forks can be customized as 340~830mm



技术参数

TECHNICAL DATA

特性 Identification	产品型号 Model		CDSD10						
	配置号 Config-code		A10/A15						
	驱动形式 Drive Unit		半电动 Semi-electric						
	驾驶方式 Operation type		步行式 Pedestrian						
	额定载重 Load capacity	Q	kg	1000/1500					
基本尺寸 Dimension	载荷中心 Load center	C	mm	600					
	总长 Overall length	L	mm	1820(A10)/1837(A15)					
	总宽 Overall width	b	mm	800	800	800	1000	1000	1000
	总高 Overall height	H2	mm	2090	1800	2025	2125	2225	2325
	起升高度 Lift height	H	mm	1600	2450	2900	3100	3300	3500
	作业时最大高度 Max working height	H1	mm	2090	2980	3430	3630	3830	4030
	货叉最小离地高度 Lowered fork height	h	mm	90					
	货叉尺寸 Fork dimensions	L1 x b2 x m	mm	1150 x 160 x 56					
	货叉外宽 Maximum fork width	b1	mm	540					
	轴距 Wheelbase	Y	mm	1133					
转弯半径 Turning radius	Wa	mm	1500						
性能 Performance	提升速度 Lift speed	满载 Loaded	mm/s	80					
		空载 Unloaded	mm/s	133					
	下降速度 Lowering speed	满载 Loaded	mm/s	113					
		空载 Unloaded	mm/s	103					
电机 Electric Motor	提升电机功率 Lift motor power		KW	1.5					
	蓄电池容量/电压 Battery capacity/voltage		Ah/V	120/12					
重量 Weight	自重(不含电池) Weight without battery	A10	kg	380	447	471	485	494	503
		A15	kg	440	507	531	545	554	563
	电池重量 Battery weight		kg	27.5					

注：最小堆垛通道Ast的计算请参考附录 Note: Min. stacking aisle width(Ast), please refer to Appendix