

Security&Signal Equipment Engineer



SUPER BRIGHTNESS LED WARNING LIGHTS

# LL109H Extra

#### SUPER BRIGHTNESS SURFACE MOUNTING LED WARNINGLIGHT

Security&Signal Equipment Engineer

Senken Group Co.,Ltd 160,West Yue Le Street,WenZhou Tel:+86-577-88090011 Fax:+86-577-88098159 E-mail:export@senken.com.cn www.senken-internationl.com

LL109H Gen3 LED warning light is specially designed with moisture and vibration resistant. Perfect for mounting in the grille, on the side mirrors and the side doors, bumpers and any other positions where warning signal is required. Suitably fitting on the police car, motorcycle, farm vehicle, lift truck, ambulance and so on.

# Aluminium Mounting Base Foamed Rubber Pad Stainless steel screw

#### Features:

• Extra powerful Gen3 LEDs as light source and specially designed optical fresnel lens to deliver high brightness at wide angles.

Clear PC lens

- Epoxy potted circuit board with high anti-impact and water-proof performance.
- Sync technology used to allow four lights to flash simultaneously or alternately.
- Total 12 flash patterns could be applied.
- · Certified by EMC Reg10 and ECE Reg65.

## **Technical Specifications:**

Color temperature:	6300
Power dissipation:	8.5W
Operation voltage range:	10Vdc-30Vdc
Dual voltage:	12Vdc-24Vdc
Current Consumption:	12Vdc/ 500 Amps
	24Vdc/ 280 amps
# of LEDs:	8 Gen3 LEDs
Light sync technology:	YES
Operation temperature:	-40 °C to +65 °C
Dimensions (Length ×width ×height):	$4.53 \times 3.0 \times 1.18$ (unit=inch)







## **Colour Options**



### Flash Pattern: 12

- 1. Quad flash (75 f/m)
- 2. Single flash(75 f/m)
- 3. Double flash(75 f/m)
- 4. Three consecutive flash(75 f/m)
- 5. Quad flash (125 f/m)
- 6. Double flash(125 f/m)
- 7. Single flash(125 f/m)
- 8. Double flash and Single flash (125 f/m)
- 9. Single flash 1 and Single flash 2(75 f/m)
- 10. Quad flash and Single flash (75 f/m)
- 11. Slow Double flash(125 f/m)
- 12. Three consecutive flash(125 f/m)

# Wiring & Mounting Schematic



