



Type\ Parameter	Filter Dia. (Ring)	Quantity of ceramic plates	Cubage of Groove (M ³)	Installation Power (KW)	Weight of Equipment (T)	Motion Power (KW)	Length of Main Engine (M)	Width of Main Engine (M)	Height of Main Engine (M)
RX-1	1	12	0.21	3.5	1	2.0	1.6	1.4	1.5
RX-4	2	24	1.0	7.0	2.0	3.0	2.4	2.5	2.1
RX-6	2	24	1.2	7.0	3.0	6.0	2.4	2.9	2.5
RX-9	3	36	1.7	9	3.5	7.0	2.7	2.9	2.5
RX-12	4	48	2.2	11	4.0	7.5	3.0	2.9	2.5
RX-15	5	60	2.7	11.5	4.5	8.0	3.3	3.0	2.5
RX-21	7	84	4.0	13.5	9	9	4.6	3.0	2.6
RX-24	8	96	4.5	16.5	9.5	10.5	4.9	3.0	2.6
RX-27	9	108	5.0	17	10	11	5.2	3.0	2.6
RX-30	10	120	5.5	17.5	10.5	11.5	5.5	3.0	2.6
RX-36	12	144	7.0	23	11.5	16	6.6	3.0	2.6
RX-45	15	180	8.5	25	13	19	7.5	3.0	2.6
RX-60	15	180	12.5	33	17	22	7.5	3.3	3.0
RX-80	20	240	16.2	40	19	24	9.0	3.3	3.0
RX-100	20	240	18.5	53	25.0	35	11.0	3.6	3.3
RX-120	24	288	22.0	60	30.0	40	12.2	3.6	3.3
RX-204	17	255	50	132	58	96	11.06	5.2	4.8
RX-240	20	300	65	145	62	100	12.26	5.2	4.906