

Double Cone Efficient Mixer specifications:

Model	Mixing cylinder volume (m³)	loading coefficient	Motor power (kw)	Outline dimension L×W×H(mm)	Weight (kg)
ZX-0.002	0.002	30-50	0.09	500×200×300	40
ZX-0.005	0.005	30-50	0.2	650×250×450	60
ZX-0.01	0.01	30-50	0.37	800×300×650	100
ZX-0.02	0.02	30-50	0.55	980×400×850	180
ZX-0.05	0.05	30-50	0.75	1350×500×1100	380
ZX-0.1	0.1	30-50	1.1	1580×650×1350	550
ZX-0.2	0.2	30-50	1.5	1800×750×1650	680
ZX-0.3	0.3	30-50	2.2	2050×850×1850	800
ZX-0.4	0.4	30-50	3	2300×950×2000	1000
ZX-0.5	0.5	30-50	3	2400×1050×2100	1200
ZX-0.8	0.8	30-50	4	2500×1200×2300	1400
ZX-1	1	30-50	4	2800×1500×2500	1800
ZX-2	2	30-50	5.5	3400×1600×2700	2100
ZX-3	3	30-50	7.5	3500×1680×2900	2400
ZX-4	4	30-50	7.5	3600×1800×3100	2600
ZX-5	5	30-50	11	3900×1900×3300	2800
ZX-6	6	30-50	11	4100×2000×3500	3000
ZX-8	8	30-50	15	4300×2200×3700	4000

For more detail info, please feel free to visit our website <http://www.fecrco.com/ZX-type-high-efficient-double-cone-mixer.html> or inquire us at yingli@magnets.com.cn at any of your convenience.