

DP-ST5001 DLP Projector

Accessories and Lenses

| | |
|-----------------------------|---------------------------|
| Supplied Accessories | Remote Control x 1, |
| | Power cable(1.8m) x1 |
| | VGA(D-sub) cable(1.8m) x1 |
| | User-Manual x1(CD-ROM) |
| | AAA battery x2 |

Replacemnt Parts

| | |
|-----------------------|-----------------------|
| Lamp | Option Lamp Available |
| Remote Control | HL03031 |
| Filter | UX38841 |
| Remote | HL03031 |
| Filter | UX38841 |



| | | |
|----------------------------|-------------------------------------|--|
| Display & Lens | Projection Technology | 0.55" 1-Chip DMD, 12deg.LVDS, DDP4421 |
| | Resolution | 1024 x 768 (Total 786,432 pixels) |
| | Brightness | Marketing Spec: 3000lm (Normal Mode), Min: 2400lm (Normal Mode) |
| Operation | Contrast Ratio | 3000 : 1 (on/off) |
| | Projection Lens | f= 5.445mm@87.2 inch, F=2.7 , 0.97m@100" |
| | Throw Ratio (Distance:Width) | 0.6:1 |
| | Off set axis | 6.7~ 9:-1 |
| | Display Size | 60 -150 inch |
| | Power consumption | Normal:350W Standby(Low):0.5W |
| | Source Lamp | Normal Mode: 240W(Unishape pro) (Shut Off Time: 3000hrs*), Low Mode:190W (Shut Off Time: 5000hrs) |
| Compatibility | Power Supply | AC100-120V/ AC220-240V,50/60Hz |
| | Operating Temperature | Operating Temperature |
| | Fan Noise | 34dB (Low Mode 32dB)、Sea-level |
| | Scanning Rate | [H] 15 - 105 kHz; [V] 50 - 120 Hz ; [Dot clock] max.165 MHz |
| | Audio Speaker | 15W Mono |
| | Height Adjuster | Screw type Front leg (0 to 7 degree variable) |
| | Digital keystone-correction | +/- 40 degree (Vertical only) |
| | IR receiver | Frontx1 |
| | PC Compatibility | 640 x480(Expand) 1024 x 768(Real) 1600 x 1200 (Compressed), NTSC / NTSC 4.43 / PAL (including PAL-M, N) / SECAM / PAL-60 |
| | Video Compatibility | Component Video : 480i/p(525i/p), 576i/p(625i/p), 720p(750p), 1080i/p(1125i/p 60Hz), 1080i/p(1125i/p 50Hz) |
| Connectors | Language Compatibility | 20 Language OSD : English/ Dutch/French / Spanish/Italian/ Korean /Thai /Portuguese/ T. Chinese/ S. Chinese/ Japanese /Russian /German /Swedish /Turkish / Finnish / Polish / Indonesian / India / Arabic |
| | Input Terminals | RGB ; mini D-sub 15pin x 2 Video ; RCA x 1 + S-VIDEO x 1 Digital ; HDMI x1 Audio ; Stereo mini jack (φ3.5mm) x 2 |
| | Output Terminal | RGB ; mini D-sub 15pin x 1 Audio ; Stereo mini jack (φ3.5mm) x 1 |
| Rating&Warranty | Communication Terminal | RS232C; mini D-sub 9pin x 1;LAN (RJ-45) ; x 1 (Projector control) USB (Type A x1): for WiFi dongle, USB reader USB (Type B x1): for FW download/Page Up/Down mini USB (Type B x1): for USB display---Optional |
| | Dimension | 319 x 102 x 223 mm (W xHx D) , Not included protrusion |
| | Weight | 3 kg(7.6 lbs) |
| | Package Dimension | 365x190x320 mm (W xHx D) |
| | Package Weight | 3.8 Kg (9.7 lbs) |
| Notice | Approvals | FCC CCC |
| | Warranty | Projector/ lamp :2 Years/6 month** Extended Service Contract available(additional cost) |
| | | * Actual lamp life will vary by individual filter based on enviroment conditions, selected operating mode,, user setting and usage, Houres of average lamp specified are not guaranteed and do not constitute part of the product warranty. Lamp brightness decreases over time ** Where a lamp fails within warranty and a replacement lamp will be maximum of 6 mounths(dependont on warranty hours stated. The pecification above and photography is for reference nly and maby be subject to change |

sales@4szqianpu.com
WWW.szqiangpu.com