

SPECIFICATIONS

	Model No.	8842AU	8843AU	8846AU	8847AU	8849AU
Camera	Imaging Sensor	CMOS				
	Total Pixels	704 x 576 (PAL) 712 x 486(NTSC)	640 x 480 (PAL) 640 x 480 (NTSC)	640 x 480	320 x 240	720 x 525 (NTSC) 720 x 625 (PAL)
	Horizontal Viewing Angle	50°	36°	35°	63°	48°
	Transmission Frequency	2468MHz				
	Minimum Illumination	0 Lux				
	Modulation Type	FM				
	Bandwidth	18MHz				
	Power Supply	4 x AA batteries				
	Unobstructed Effective Range	10m (max.)				
	Waterproof Capacity	IP67 (for lens/tube only)				
	Tube Diameter	17mm	9mm	17mm	4.5mm	5.5mm
	Dimensions (W x D x H)	260 x 108 x 71(mm) (Excluding Flexible Tube)				
	Approx. Weight	540g	476g	538g	288g	366g
Monitor	LCD Screen Type	3.5" TFT-LCD				
	Effective Pixels	320(R.G.B) x 240				
	Video System	PAL/NTSC				
	Transmission Frequency	2468MHz				
	Exterior Supply Voltage	9VDC				
	Consumption Current (Max.)	500mA				
	Charging Time	2.5 hours				
	Working Time	2 hours				
	Picture/Video Pixels	640 x 480				
	Video Format	.AVI				
	Picture Format	.JPG				
	Frame Rate	30 frame/second				
	Receiving Sensitivity	≤-85dBm				
	Dimensions (W x D x H)	106 x 89 x 37 (mm)				
	Approx. Weight	232g				
	Operating Temperature	-10°C-50°C/14°F-122°F				
	Operating Humidity (Max.)	15~85%RH				