

# Gas Leakage Detector

## Introduction :

The Gas Leakage Detector detects the presence of potentially harmful propane butane, acetylene and methane (natural gas). Activation of the detector's visible and audible signals indicate the presence of combustible gases. Careful use of this detector will provide years of reliable service.

## Specifications :

Model no.:	MS-GLD3
Measurement ranges	0 - 10,000 ppm
Operating voltage	3V DC
Max. operating current	<200mA
Operating conditions	10°C-50°C;<95% RH
Storage conditions	5°C-55°C;<95% RH
Power On	Press and hold for 3 seconds
Auto power off	After approximate 3 minutes
Indications	Green:Power ON with short beep/Safe with no alarm Yellow:Lo alarm with short beep>2000ppm (0.2%) of methane(natural gas) detected Red:Hi alarm with long beep>4000ppm (0.4%) of methane(natural gas) detected
Low battery indication	Green LED blinks continuously or no LED lights up
Detectable gas	Propane, Butane, Acetylene, Methane (Natural Gas)
Calibration	No calibration required
Battery powered	2 AAA / LR03
Dimension (L x W x D) mm	165x27x26
Weight (approx.) grams	44 (without battery)



**MEET INTERNATIONAL LTD.** MANUFACTURER AND EXPORTER

Flat C, 11/F., China Trade Centre, 122-124 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong.

Tel : (852) 2950 4689

E-mail : [sales@meet.com.hk](mailto:sales@meet.com.hk)

Website : [www.meet.com.hk](http://www.meet.com.hk)

[www.globalsources.com/meetintl.co](http://www.globalsources.com/meetintl.co)

[www.meetusa.en.alibaba.com](http://www.meetusa.en.alibaba.com)

Copyright © 2016 Meet International Ltd. All rights reserved