

单相制动电机

Single-Phase Brake Motor

性能特点:

- 功率: 1/3HP-2HP
- 极数: 4P
- 机座号: 56C
- 防护形式: 封闭式
- 防护等级: IP44
- 服务系数: 1.15
- 适用于有制动要求的场合, 如快速停车、升降机、卷扬机等
- 均通过 CSA & CUS 安全认证

Features:

- HP: 1/3HP-2HP
- Pole: 4P
- Frame: 56C
- Enclosure: TEFC
- IP Class: IP44
- Service Factor: 1.15
- Apply to Auto requirement situations, such as : sudden parking, elevator, windlass, etc;
- CSA&CUS certified

HP	RPM 60HZ	NEMA FRAME	Model	Volts	HZ	ENCL.	S.F	Full Load AMPS	WGT. LBS.
1/3	1800	56C	F56C1/3S4C-2	115/208-230	60	TEFC	1.15	4.29/2.06-2.26	27
1/2	1800	56C	F56C1/2S4C-2	115/230	60	TEFC	1.15	5.8/2.9	29
3/4	1800	56C	F56C3/4S4C-2	115/208-230	60	TEFC	1.15	8.07/4.04-4.17	33
1	1800	56C	F56C1S4C-2	115/208-230	60	TEFC	1.15	9.3/5.18-4.78	42
1.5	1800	56C	F56C1.5S4C-2	115/230	60	TEFC	1.15	14/6.8	48
2	1800	56C	F56C2S4C-2	115/208-230	60	TEFC	1.15	16.51/9.08-8.27	51