

H Beam Specification						
Category (mm)	Specification (mm)	Section Dimension (mm)				GB Weight (kg/m)
		H	B	T1	T2	
HW	100*100	100	100	6	8	17.2
	125*125	125	125	6.5	9	23.8
	150*150	150	150	7	10	31.9
	175*175	175	175	7.5	11	40.3
	200*200	200	200	8	12	50.5
		200	204	12	12	56.7
	250*250	250	250	9	14	72.4
		250	255	14	14	82.2
HM	150*100	148	100	6	9	21.4
	200*150	194	150	6	9	31.2
	250*175	244	175	7	11	44.1
	300*200	294	200	8	12	57.3
	350*250	340	250	9	14	79.7
	600*300	582	300	12	17	137
		588	300	12	20	151
		594	302	14	23	175
HN	150*75	150	75	5	7	14.3
	175*90	175	90	5	8	18.2
	200*100	198	99	4.5	7	18.5
		200	100	5.5	8	21.7
	250*125	248	124	5	8	25.8
		250	125	6	9	29.7
	300*150	298	149	5.5	8	32.6

		300	150	6.5	9	37.3
	350*175	350	175	7	11	50
	400*150	400	150	8	13	55.8
	400*200	396	199	7	11	56.7
		400	200	8	13	66
	450*150	450	150	9	14	65.5
	450*200	446	199	8	12	66.7
		450	200	9	14	76.5
	500*150	500	150	10	16	77.1