



Model: 8129U

Continuous power(持续功率): 800W
Peak power(峰值功率): 1600W
Input voltage(输入电压): DC 12V, DC 24V
Output voltage(输出电压): AC 100V -120V
Frequency(频率): 60 +/- 3HZ
USB output(USB输出): DC 5V (0.5A, 1A, 2.1A)
Output waveform(输出波形): Modified sine wave



Protection Specification(保护功能):
Overload Protection
Overheat Protection
Input Overvoltage Protection
Input Lowvoltage Protection
Output Short-circuit Protection

Size(产品尺寸): 255×185×85mm
Packing(包装): Color box, 8pcs/ctn
G.W.: 17.6kgs, N.W.: 16.8kgs
Meas: 51×31.5×48.5cm/ctn



Model: 8130U

Continuous power(持续功率): 1000W
Peak power(峰值功率): 2000W
Input voltage(输入电压): DC 12V, DC 24V
Output voltage(输出电压): AC 100V -120V
Frequency(频率): 60 +/- 3HZ
USB output(USB输出): DC 5V (0.5A, 1A, 2.1A)
Output waveform(输出波形): Modified sine wave



Protection Specification(保护功能):
Overload Protection
Overheat Protection
Input Overvoltage Protection
Input Lowvoltage Protection
Output Short-circuit Protection

Size(产品尺寸): 255×185×85mm
Packing(包装): Color box, 8pcs/ctn
G.W.: 17.6kgs, N.W.: 16.8kgs
Meas: 51×31.5×48.5cm/ctn



Model: 8131U

Continuous power(持续功率): 1200W
Peak power(峰值功率): 2400W
Input voltage(输入电压): DC 12V, DC 24V
Output voltage(输出电压): AC 100V -120V
Frequency(频率): 60 +/- 3HZ
USB output(USB输出): DC 5V (0.5A, 1A, 2.1A)
Output waveform(输出波形): Modified sine wave



Protection Specification(保护功能):
Overload Protection
Overheat Protection
Input Overvoltage Protection
Input Lowvoltage Protection
Output Short-circuit Protection

Size(产品尺寸): 307×185×85mm
Packing(包装): Color box, 5pcs/ctn
G.W.: 14.4kgs, N.W.: 13.6kgs
Meas: 63×36.5×25.5cm/ctn



Model: 8132U

Continuous power(持续功率): 1500W
Peak power(峰值功率): 3000W
Input voltage(输入电压): DC 12V, DC 24V
Output voltage(输出电压): AC 100V -120V
Frequency(频率): 60 +/- 3HZ
USB output(USB输出): DC 5V (0.5A, 1A, 2.1A)
Output waveform(输出波形): Modified sine wave



Protection Specification(保护功能):
Overload Protection
Overheat Protection
Input Overvoltage Protection
Input Lowvoltage Protection
Output Short-circuit Protection

Size(产品尺寸): 307×185×85mm
Packing(包装): Color box, 5pcs/ctn
G.W.: 14.6kgs, N.W.: 13.8kgs
Meas: 63×36.5×25.5cm/ctn



Model: 8033U

Continuous power(持续功率): 300W
Peak power(峰值功率): 600W
Input voltage(输入电压): DC 12V, DC 24V
Output voltage(输出电压): AC 220V-240V/AC 110V-120V
Frequency(频率): 50 +/- 3HZ, 60 +/- 3HZ
USB Output(USB输出): DC 5V (0.5A, 1A, 2.1A)
Output waveform(输出波形): Modified sine wave

Protection Specification(保护功能):
Overload Protection
Overheat Protection
Input Overvoltage Protection
Input Lowvoltage Protection
Output Short-circuit Protection

Size(产品尺寸): 180×102×55mm
Packing(包装): Blister, 20pcs/ctn
G.W.: 19kgs, N.W.: 18kgs
Meas: 57.5×34×45cm/ctn




Model: 8034U

Continuous power(持续功率): 400W
Peak power(峰值功率): 800W
Input voltage(输入电压): DC 12V, DC 24V
Output voltage(输出电压): AC 220V-240V/AC 110V-120V
Frequency(频率): 50 +/- 3HZ, 60 +/- 3HZ
USB Output(USB输出): DC 5V (0.5A, 1A, 2.1A)
Output waveform(输出波形): Modified sine wave

Protection Specification(保护功能):
Overload Protection
Overheat Protection
Input Overvoltage Protection
Input Lowvoltage Protection
Output Short-circuit Protection

Size(产品尺寸): 180×102×55mm
Packing(包装): Blister, 20pcs/ctn
G.W.: 19.3kgs, N.W.: 17.3kgs
Meas: 57.5×34×45cm/ctn




Model: 8035U

Continuous power(持续功率): 500W
Peak power(峰值功率): 1000W
Input voltage(输入电压): DC 12V, DC 24V
Output voltage(输出电压): AC 220V-240V/AC 110V-120V
Frequency(频率): 50 +/- 3HZ, 60 +/- 3HZ
USB Output(USB输出): DC 5V (0.5A, 1A, 2.1A)
Output waveform(输出波形): Modified sine wave

Protection Specification(保护功能):
Overload Protection
Overheat Protection
Input Overvoltage Protection
Input Lowvoltage Protection
Output Short-circuit Protection

Size(产品尺寸): 230×102×55mm
Packing(包装): Blister, 20pcs/ctn
G.W.: 26.0kgs, N.W.: 24kgs
Meas: 57.5×34×45cm/ctn



Model: 8036U

Continuous power(持续功率): 600W
Peak power(峰值功率): 1200W
Input voltage(输入电压): DC 12V, DC 24V
Output voltage(输出电压): AC 220V-240V/AC 110V-120V
Frequency(频率): 50 +/- 3HZ, 60 +/- 3HZ
USB Output(USB输出): DC 5V (0.5A, 1A, 2.1A)
Output waveform(输出波形): Modified sine wave

Protection Specification(保护功能):
Overload Protection
Overheat Protection
Input Overvoltage Protection
Input Lowvoltage Protection
Output Short-circuit Protection

Size(产品尺寸): 230×102×55mm
Packing(包装): Blister, 20pcs/ctn
G.W.: 26.5kgs, N.W.: 24.5kgs
Meas: 57.5×34×45cm/ctn






Model: 8800

Continuous power(持续功率): 800W
Peak power(峰值功率): 1600W
Input voltage(输入电压): DC 12V,DC 24V
Output voltage(输出电压): AC 220V-240V/AC 110V-120V
Frequency(频率): 50+/-3HZ,60+/-3HZ
Output waveform(输出波形): Modified sine wave

Protection Specification(保护功能):
Overload Protection
Overheat Protection
Input Overvoltage Protection
Input Lowvoltage Protection
Output Short-circuit Protection

Size(产品尺寸):230×130×65mm
Packing(包装):Color box, 10pcs/ctn
G.W.:21.5kgs, N.W.:20.5kgs
Meas:56×30.5×35cm/ctn




Model: 81000

Continuous power(持续功率): 1000W
Peak power(峰值功率): 2000W
Input voltage(输入电压): DC 12V,DC 24V
Output voltage(输出电压): AC 220V-240V/AC 110V-120V
Frequency(频率): 50+/-3HZ,60+/-3HZ
Output waveform(输出波形): Modified sine wave

Protection Specification(保护功能):
Overload Protection
Overheat Protection
Input Overvoltage Protection
Input Lowvoltage Protection
Output Short-circuit Protection

Size(产品尺寸):250×130×65mm
Packing(包装):Color box, 10pcs/ctn
G.W.:22kgs, N.W.:21kgs
Meas:56×30.5×35cm/ctn




Model: 81200

Continuous power(持续功率): 1200W
Peak power(峰值功率): 2400W
Input voltage(输入电压): DC 12V,DC 24V
Output voltage(输出电压): AC 220V-240V/AC 110V-120V
Frequency(频率): 50+/-3HZ,60+/-3HZ
Output waveform(输出波形): Modified sine wave

Protection Specification(保护功能):
Overload Protection
Overheat Protection
Input Overvoltage Protection
Input Lowvoltage Protection
Output Short-circuit Protection

Size(产品尺寸):250×130×65mm
Packing(包装):Color box, 10pcs/ctn
G.W.:23kgs, N.W.:22kgs
Meas:56×30.5×35cm/ctn



Model: 81500

Continuous power(持续功率): 1500W
Peak power(峰值功率): 3000W
Input voltage(输入电压): DC 12V,DC 24V
Output voltage(输出电压): AC 220V-240V/AC 110V-120V
Frequency(频率): 50+/-3HZ,60+/-3HZ
Output waveform(输出波形): Modified sine wave

Protection Specification(保护功能):
Overload Protection
Overheat Protection
Input Overvoltage Protection
Input Lowvoltage Protection
Output Short-circuit Protection

Size(产品尺寸):280×130×65mm
Packing(包装):Color box, 8pcs/ctn
G.W.:21kgs, N.W.:20kgs
Meas:45.5×30.5×35cm/ctn




Model: 82000

Continuous power(持续功率): 2000W
Peak power(峰值功率): 4000W
Input voltage(输入电压): DC 12V,DC 24V
Output voltage(输出电压): AC 220V-240V/AC 110V-120V
Frequency(频率): 50+/-3HZ,60+/-3HZ
USB Output(USB输出): DC 5V (0.5A, 1A, 2.1A)
Output waveform(输出波形): Modified sine wave

Protection Specification(保护功能):
Overload Protection
Overheat Protection
Input Overvoltage Protection
Input Lowvoltage Protection
Output Short-circuit Protection

Size(产品尺寸):420×200×102mm
Packing(包装):Color box, 3pcs/ctn
G.W.:17.7kgs, N.W.:16.7kgs
Meas:49×42.5×25cm/ctn




Model: 82500

Continuous power(持续功率): 2500W
Peak power(峰值功率): 5000W
Input voltage(输入电压): DC 12V,DC 24V
Output voltage(输出电压): AC 220V-240V/AC 110V-120V
Frequency(频率): 50+/-3HZ,60+/-3HZ
USB Output(USB输出): DC 5V (0.5A, 1A, 2.1A)
Output waveform(输出波形): Modified sine wave

Protection Specification(保护功能):
Overload Protection
Overheat Protection
Input Overvoltage Protection
Input Lowvoltage Protection
Output Short-circuit Protection

Size(产品尺寸):420×200×102mm
Packing(包装):Color box, 3pcs/ctn
G.W.:19.3kgs, N.W.:18.3kgs
Meas:49×42.5×25cm/ctn




Model: 83000

Continuous power(持续功率): 3000W
Peak power(峰值功率): 6000W
Input voltage(输入电压): DC 12V,DC 24V
Output voltage(输出电压): AC 220V-240V/AC 110V-120V
Frequency(频率): 50+/-3HZ,60+/-3HZ
USB Output(USB输出): DC 5V (0.5A, 1A, 2.1A)
Output waveform(输出波形): Modified sine wave

Protection Specification(保护功能):
Overload Protection
Overheat Protection
Input Overvoltage Protection
Input Lowvoltage Protection
Output Short-circuit Protection

Size(产品尺寸):420×200×102mm
Packing(包装):Color box, 3pcs/ctn
G.W.:19.5kgs, N.W.:18.5kgs
Meas:49×42.5×25cm/ctn



Model: 85000

Continuous power(持续功率): 5000W
Peak power(峰值功率): 10000W
Input voltage(输入电压): DC 24V
Output voltage(输出电压): AC 220V-240V/AC 110V-120V
Frequency(频率): 50+/-3HZ,60+/-3HZ
USB Output(USB输出): DC 5V (0.5A, 1A, 2.1A)
Output waveform(输出波形): Modified sine wave

Protection Specification(保护功能):
Overload Protection
Overheat Protection
Input Overvoltage Protection
Input Lowvoltage Protection
Output Short-circuit Protection

Size(产品尺寸):355×250×180mm
Packing(包装):Corrugated Carton, 1pc/ctn
G.W.:10kgs, N.W.:9.5kgs
Meas:39×31.5×25cm/ctn

