

<b>Product Name</b>	Cat6 Modular Plug for Flat Cable UTP
<b>Model No</b>	EXW-001
<b>Origin</b>	Ningbo, China
<b>Brand Name</b>	EXW or OEM case.
<b>Packing</b>	100pcs/bag, 5000pcs/inner box, 2 inner boxes / carton.
<b>Unit price</b>	0.1~0.2 USD/pcs.
<b>Delivery Time</b>	3~4 weeks, urgent order: within 2 weeks.
<b>MOQ</b>	5,000pcs
<b>Capability</b>	1,000,000pcs/day
<b>Certificate</b>	ISO9001:2001 / ISO14001 / OHSAS18001 / UL / RoHS / REACH.

**Product Description:**

1. **Product Name:** Cat6 Modular Plug for Flat Cable UTP
  
2. **Suitable for cat6 UTP cable:** Flat, and stranded cable 26~30AWG;
  
3. **Contact blade:** Copper Alloy with gold plating 50u, the standard gold thickness 03U, 06u, 15u, 30u, 50u could be optional.
  
4. **Blade Type:** 3 prongs Z blade.
  
5. **Housing Material:** Japan Teijin PC, UL 94-V2, UL 94-V0 is available.
  
6. **Color:** Transparent, Transparent color blue, red etc., or not transparent blue, red etc., 3 options .
  
7. **Mechanical:** Fully comply with FCC standard.
  - 7.1 Cable to plug strength 25 POUND MIN.
  - 7.2 Durability: mating cycle 750 operations.

## 8. Electrical:

UL Applications: 250 VOLTS AC MAX, AT 2 AMPS.

Dielectric Withstanding voltage: 500 VOLTS AC.

Insulation Resistance: 100MΩ

Termination test: Resistance 20mΩ max after environmental testing.

## 9. Packing rate:

SPEC.	Q'TY PCS/CTN	N.W. KGS	G.W. KGS	Dimension(cm)
6P2C	20,000	15.96	17.50	49.6*36.2*26.5
6P4C	20,000	15.86	17.40	49.6*36.2*26.5
6P6C	20,000	16.13	18.03	49.6*36.2*26.5
4P4C	25,000	16.59	18.23	49.6*36.2*26.5
8P8C	10,000	15.26	17.00	49.6*36.2*26.5
8P Shielded	10,000	25.40	27.50	51.6*36.2*32.0
Cat.6 UTP	10,000	13.70	15.80	51.6*36.2*32.0
Cat.6 Shielded	10,000	23.72	25.82	51.6*36.2*32.0

10. Packing picture: 1000pcs/bag, or 100PCS/bag is optional;



11. Quality Control: AOI system (Automatic Optical Inspection);

