

SBW-F-50KVA-2000KVA Three Phase Voltage Regulator



Product description					
MODEL	SBW-F-50KVA	SBW-F-75KVA	SBW-F-100KVA	SBW-F-150KVA	SBW-F-200KVA
	SBW-F-250KVA	SBW-F-320KVA	SBW-F-400KVA	SBW-F-500KVA	SBW-F-600KVA
	SBW-F-800KVA	SBW-F-1000KVA	SBW-F-1200KVA	SBW-F-1500KVA	SBW-F-2000KVA
TECHNOLOGY	SERVO MOTOR CONTROL SYSTEM				
DISPLAY	METER	A/B/C PHASE INPUT VOLTAGE			
		A/B/C PHASE OUTPUT VOLTAGE			
		A PHASE OUTPUT CURRENT			
		B PHASE OUTPUT CURRENT			
		C PHASE OUTPUT CURRENT			
	Light	Green	A PHASE WORKING INDICATOR		
		Green	B PHASE WORKING INDICATOR		
		Green	C PHASE WORKING INDICATOR		
		Green	INPUT WORKING INDICATOR		
		Green	INPUT WORKING INDICATOR		
	Language	English/Russia/Chinese			
Input Voltage	Single phase:175V-265V Three phase four-line 175V-265V(phase voltage)300V-465V (line voltage)				

	154V-286V(phase voltage) 270V-490v(line voltage)				
Output Voltage	Single phase 220V(Adjustable) three phase 380V(adjustable)				
Frequency	50Hz/60Hz				
Phase	Thee phase				
Efficiency	$\geq 90\%$				
Ambient Temperature	$-15^{\circ}\text{C}-45^{\circ}\text{C}$				
Relative humidity	$<95\%$				
Waveform distortion	No additional wave from distortion				
Insulation resistance	Normally more than $2\text{M}\Omega$				
Power	50KVA	75KVA	100KVA	150KVA	200KVA
Packing size(cm)	110*85*137	110*85*137	110*85*137	125*100*196	125*100*196
Packing (pcs)	1	1	1	1	1
G. M (KGS)					
Power	250KVA	320KVA	400KVA	500KVA	600KVA
Packing size(cm)	135*100*196	135*100*196			
Packing (pcs)	1	1	1	1	1
G. M (KGS)					