



Model: 8030U

Max power(最大功率): 75W(10min)
Continuous power(持续功率): 60W
Peak power(峰值功率): 150W
Input voltage(输入电压): DC 12V
Output voltage(输出电压): AC 100V - 120V / AC 220V - 240V
Frequency(频率): 60 +/- 3Hz, 50 +/- 3Hz
USB output(USB输出): DC 5V (0.5A, 1A, 2.1A)
Output waveform(输出波形): Modified sine wave

Protection Specification(保护功能):
Overload Protection
Overheat Protection
Input Overvoltage Protection
Input Lowvoltage Protection
Output Short-circuit Protection

Size(产品尺寸): 125*60*35mm
Packing(包装): Blister, 50pcs/ctn
G.W.: 11.6kg, N.W.: 8.6kg
Meas.: 47.5*29*57cm/ctn



Model: 8032U

Max power(最大功率): 75W(10min)
Continuous power(持续功率): 60W
Peak power(峰值功率): 150W
Input voltage(输入电压): DC 12V
Output voltage(输出电压): AC 100V - 120V / AC 220V - 240V
Frequency(频率): 60 +/- 3Hz, 50 +/- 3Hz
USB output(USB输出): DC 5V (0.5A, 1A, 2.1A)
Output waveform(输出波形): Modified sine wave

Protection Specification(保护功能):
Overload Protection
Overheat Protection
Input Overvoltage Protection
Input Lowvoltage Protection
Output Short-circuit Protection

Size(产品尺寸): 130*60*40mm
Packing(包装): Blister, 50pcs/ctn
G.W.: 12.5kg, N.W.: 10.5kg
Meas.: 47.5*29*57cm/ctn



Model: 8175U

Continuous power(持续功率): 175W
Peak power(峰值功率): 350W
Input voltage(输入电压): DC 12V
Output voltage(输出电压): AC 100V - 120V / AC 220V - 240V
Frequency(频率): 60 +/- 3Hz, 50 +/- 3Hz
USB output(USB输出): DC 5V (0.5A, 1A, 2.1A)
Output waveform(输出波形): Modified sine wave

Protection Specification(保护功能):
Overload Protection
Overheat Protection
Input Overvoltage Protection
Input Lowvoltage Protection
Output Short-circuit Protection

Size(产品尺寸): 130*75*50mm
Packing(包装): Blister, 40pcs/ctn
G.W.: 11.5kg, N.W.: 8.7kg
Meas.: 56.5*35*37.5cm/ctn



Model: 8081N

Continuous power(持续功率): 150W
Peak power(峰值功率): 300W
Input voltage(输入电压): DC 12V
Output voltage(输出电压): AC 100V - 120V / AC 220V - 240V
Frequency(频率): 60 +/- 3Hz, 50 +/- 3Hz
USB output(USB输出): DC 5V (0.5A, 1A)
Output waveform(输出波形): Modified sine wave

Protection Specification(保护功能):
Overload Protection
Overheat Protection
Input Overvoltage Protection
Input Lowvoltage Protection
Output Short-circuit Protection

Size(产品尺寸): 113*85*30mm
Packing(包装): Blister, 40pcs/ctn
G.W.: 12.5kg, N.W.: 10.4kg
Meas.: 47.5*29*57cm/ctn



Model: 8023U

Continuous power(持续功率): 150W
Peak power(峰值功率): 300W
Input voltage(输入电压): DC 12V
Output voltage(输出电压): AC 100V - 120V / AC 220V - 240V
Frequency(频率): 60 +/- 3Hz, 50 +/- 3Hz
USB output(USB输出): DC 5V (0.5A, 1A, 2.1A)
Output waveform(输出波形): Modified sine wave

Protection Specification(保护功能):
Overload Protection
Overheat Protection
Input Overvoltage Protection
Input Lowvoltage Protection
Output Short-circuit Protection

Size(产品尺寸): 132*75*46mm
Packing(包装): Blister, 40pcs/ctn
G.W.: 9.6kg, N.W.: 8.0kg
Meas.: 59.5*32.5*29.5cm/ctn



Model: 8023U-B

Continuous power(持续功率): 150W
Peak power(峰值功率): 300W
Input voltage(输入电压): DC 12V
Output voltage(输出电压): AC 100V - 120V / AC 220V - 240V
Frequency(频率): 60 +/- 3Hz, 50 +/- 3Hz
USB output(USB输出): DC 5V (0.5A, 1A, 2.1A)
Output waveform(输出波形): Modified sine wave

Protection Specification(保护功能):
Overload Protection
Overheat Protection
Input Overvoltage Protection
Input Lowvoltage Protection
Output Short-circuit Protection

Size(产品尺寸): 132*75*48mm
Packing(包装): Blister, 40pcs/ctn
G.W.: 12.0kg, N.W.: 10.0kg
Meas.: 59.5*38.5*37.5cm/ctn



Model: DAU-150

Continuous power(持续功率): 150W
Peak power(峰值功率): 300W
Input voltage(输入电压): DC 12V
Output voltage(输出电压): AC 100V - 120V / AC 220V - 240V
Frequency(频率): 60 +/- 3Hz, 50 +/- 3Hz
USB output(USB输出): DC 5V (0.5A, 1A, 2.1A)
Output waveform(输出波形): Modified sine wave

Protection Specification(保护功能):
Overload Protection
Overheat Protection
Input Overvoltage Protection
Input Lowvoltage Protection
Output Short-circuit Protection

Size(产品尺寸): 140*72*50mm
Packing(包装): Blister, 40pcs/ctn
G.W.: 13.4kg, N.W.: 11.4kg
Meas.: 47.5*29*57cm/ctn



Model: DAU-150-B

Continuous power(持续功率): 150W
Peak power(峰值功率): 300W
Input voltage(输入电压): DC 12V
Output voltage(输出电压): AC 100V - 120V / AC 220V - 240V
Frequency(频率): 60 +/- 3Hz, 50 +/- 3Hz
USB output(USB输出): DC 5V (0.5A, 1A, 2.1A)
Output waveform(输出波形): Modified sine wave

Protection Specification(保护功能):
Overload Protection
Overheat Protection
Input Overvoltage Protection
Input Lowvoltage Protection
Output Short-circuit Protection

Size(产品尺寸): 90*72*50mm
Packing(包装): Blister, 40pcs/ctn
G.W.: 16.2kg, N.W.: 14.2kg
Meas.: 65*34*37cm/ctn



Model 8081U

Continuous power(持续功率): 150W
Peak power(峰值功率): 300W
Input voltage(输入电压): DC 12V
Output voltage(输出电压): AC 220V-240V/AC 110V-120V
Frequency(频率): 50+/3HZ, 60+/3HZ
USB Output(USB输出): DC 5V (0.5A, 1A)
Output waveform(输出波形): Modified sine wave

Protection Specification(保护功能):
Overload Protection
Overheat Protection
Input Overvoltage Protection
Input Lowvoltage Protection
Output Short-circuit Protection

Size(产品尺寸): 107*67*45mm
Packing(包装): Blister 40pcs/ctn
G.W.: 15.5kgs, N.W.: 13.5kgs
Meas: 47.5*29*57cm/ctn



Model 8200U

Continuous power(持续功率): 200W
Peak power(峰值功率): 400W
Input voltage(输入电压): DC 12V
Output voltage(输出电压): AC 220V-240V/AC 110V-120V
Frequency(频率): 50+/3HZ, 60+/3HZ
USB Output(USB输出): DC 5V (0.5A, 1A)
Output waveform(输出波形): Modified sine wave

Protection Specification(保护功能):
Overload Protection
Overheat Protection
Input Overvoltage Protection
Input Lowvoltage Protection
Output Short-circuit Protection

Size(产品尺寸): 107*67*45mm
Packing(包装): Blister 40pcs/ctn
G.W.: 15.5kgs, N.W.: 13.5kgs
Meas: 47.5*29*57cm/ctn



Model 8081Y

Continuous power(持续功率): 150W
Peak power(峰值功率): 300W
Input voltage(输入电压): DC 12V
Output voltage(输出电压): AC 220V-240V/AC 110V-120V
Frequency(频率): 50+/3HZ, 60+/3HZ
USB Output(USB输出): DC 5V (0.5A, 1A)
Output waveform(输出波形): Modified sine wave

Protection Specification(保护功能):
Overload Protection
Overheat Protection
Input Overvoltage Protection
Input Lowvoltage Protection
Output Short-circuit Protection

Size(产品尺寸): 150*73*73mm
Packing(包装): Color box 30pcs/ctn
G.W.: 15.0kgs, N.W.: 14.0kgs
Meas: 44*41*36.5cm/ctn



Model 8200Y

Continuous power(持续功率): 200W
Peak power(峰值功率): 400W
Input voltage(输入电压): DC 12V
Output voltage(输出电压): AC 220V-240V/AC 110V-120V
Frequency(频率): 50+/3HZ, 60+/3HZ
USB Output(USB输出): DC 5V (0.5A, 1A)
Output waveform(输出波形): Modified sine wave

Protection Specification(保护功能):
Overload Protection
Overheat Protection
Input Overvoltage Protection
Input Lowvoltage Protection
Output Short-circuit Protection

Size(产品尺寸): 150*73*73mm
Packing(包装): Color box 30pcs/ctn
G.W.: 15.0kgs, N.W.: 14.0kgs
Meas: 44*41*36.5cm/ctn



Model 8201

Max power(最大功率): 200W (3 min)
Continuous power(持续功率): 100W
Peak power(峰值功率): 160W
Input voltage(输入电压): DC 12V
Output voltage(输出电压): AC 230V(+10%)
Frequency(频率): 50+/-3HZ
USB Output(USB输出): DC 5V (0.5A, 1A, 2.1A)
Output waveform(输出波形): Modified sine wave

Protection Specification(保护功能):
Overload Protection
Overheat Protection
Input Overvoltage Protection
Input Lowvoltage Protection
Output Short-circuit Protection



Model 8202

Continuous power(持续功率): 150W
Peak power(峰值功率): 300W
Input voltage(输入电压): DC 12V
Output voltage(输出电压): AC 230V(+10%)
Frequency(频率): 50+/-3HZ
USB Output(USB输出): DC 5V (0.5A, 1A, 2.1A)
Output waveform(输出波形): Modified sine wave

Protection Specification(保护功能):
Overload Protection
Overheat Protection
Input Overvoltage Protection
Input Lowvoltage Protection
Output Short-circuit Protection



Model 8203

Continuous power(持续功率): 200W
Peak power(峰值功率): 400W
Input voltage(输入电压): DC 12V
Output voltage(输出电压): AC 230V(+10%)
Frequency(频率): 50+/-3HZ
USB Output(USB输出): DC 5V (0.5A, 1A, 2.1A)
Output waveform(输出波形): Modified sine wave

Protection Specification(保护功能):
Overload Protection
Overheat Protection
Input Overvoltage Protection
Input Lowvoltage Protection
Output Short-circuit Protection



Model 8204

Continuous power(持续功率): 150W
Peak power(峰值功率): 300W
Input voltage(输入电压): DC 12V
Output voltage(输出电压): AC 230V(+10%)
Frequency(频率): 50+/-3HZ
USB Output(USB输出): DC 5V (0.5A, 1A, 2.1A)
Output waveform(输出波形): Modified sine wave

Protection Specification(保护功能):
Overload Protection
Overheat Protection
Input Overvoltage Protection
Input Lowvoltage Protection
Output Short-circuit Protection



Model 6500

Continuous power(持续功率): 200W
Peak power(峰值功率): 400W
Input voltage(输入电压): DC 12V
Output voltage(输出电压): AC 230V(+10%)
Frequency(频率): 50+/-3HZ
USB Output(USB输出): DC 5V (0.5A, 1A, 2.1A)
Output waveform(输出波形): Modified sine wave

Protection Specification(保护功能):
Overload Protection
Overheat Protection
Input Overvoltage Protection
Input Lowvoltage Protection
Output Short-circuit Protection

