

Multi Core Electric Cable

Model No.	Conductor		Insulation		Jacket		
	Cores × Nom. Area	Max. Resistance at 20°C	Thickness	Min. Resistance at 70°C	Thickness	Min. Dia.	Max.
	mm ²	MΩ/km	mm	MΩ/km	mm	mm	mm
RVV2×0.75	2×0.75	26	0.6	0.011	0.8	6	7.6
RVV2×1.0	2×1.0	19.5	0.6	0.01	0.8	6.4	8
RVV2×1.5	2×1.5	13.3	0.7	0.01	0.8	7.4	9
RVV2×2.5	2×2.5	7.98	0.8	0.009	1	8.9	11
RVV3×0.75	3×0.75	26	0.6	0.011	0.8	6.4	8
RVV3×1.0	3×1.0	19.5	0.6	0.01	0.8	6.8	8.4
RVV3×1.5	3×1.5	13.3	0.7	0.01	0.9	8	9.8
RVV3×2.5	3×2.5	7.98	0.8	0.009	1	9.6	12
RVV4×0.75	4×0.75	26	0.6	0.011	0.8	6.8	8.6
RVV4×1.0	4×1.0	19.5	0.6	0.01	0.9	7.6	9.4
RVV4×1.5	4×1.5	13.3	0.7	0.01	1	9	11
RVV4×2.5	4×2.5	7.98	0.8	0.009	1.1	10.5	13
RVV5×0.75	5×0.75	26	0.6	0.011	0.9	7.4	9.6
RVV5×1.0	5×1.0	19.5	0.6	0.01	0.9	8.3	10
RVV5×1.5	5×1.5	13.3	0.7	0.01	1.1	10	12
RVV5×2.5	5×2.5	7.98	0.8	0.009	1.2	11.5	14