



SPECIFICATION Of 6×4 Dump truck

Truck Model		ZZ3257N3447A1
Dimension(Lx W xH) (unloaded) (mm)		7835×2496×3386
Cargo body size (LxWxH) (mm)		5200x2300x1400, T middle lift, bottom 8mm, side 6mm
Approaching angle/Departure angle (°)		19/27
Overhang(front/rear) (mm)		1500/1560
Wheel base (mm)		3425+1350
Max speed (km/h)		75
Curb weight (kg)		12380
Loading Weight (kg)		12490
Engine (Steyr technology, made in China)	Model	WD615.69, water-cooled, four strokes, 6 cylinders in line with water cooling, turbocharged and intercooling, directly injection
	Fuel type	Diesel
	HorsePower, max (kw/rpm)	336HP, 247/2200
	Emission	EURO2
Fuel tanker capacity 油箱容积 (L)		300
Transmission	Model	HW19710
Brake system	Service brake	Dual circuit compressed air brake
	Parking brake	spring energy, compressed air operating on rear wheels
Steering system	Model	ZF8118

Front axle	HF9 Drum, Steering with double T-cross section beam	
Rear axle	HC16, Pressed axle housing, central double reduction with differential locks between axles and wheels	
Tyre	12.00R20, radial tire	
Electrical system	Battery	2X12V/165Ah
	Alternator	28V-1500kw
	Starter	7.5Kw/24V
Cab	HOWO76 cab, single-sleeper, all-steel forward control,55°hydraulically tiltable to the front,2- arm windscreen wiper system with three speeds, laminated windscreen with casted-in radio aerial, hydraulically damped adjustable driver's seat and rigid adjustable co-driver's seat, with heating and ventilating system, outer sun visor, adjustable roof flap, with stereo radio/cassette recorder, safety belts and adjustable steering wheel, air horn, with 4-point support fully floating suspension and shock absorbers	