

Specification:

Permanent Magnetic Lifter

Type	Rated Lifting Capacity (kg)	Dimension L*W*H(cm)	Max Breakaway Force (kg)	Net Weight (kg)	Gross Weight (kg)
JG-100	100	25*16*16	300	3	4
JG-400	400	32*20*17	1200	10	11
JG-600	600	37*23*21	1800	20	22
JG-1000	1000	43*28*24	3000	37	40
JG-2000	2000	52*30*31	5000	68	74
JG-3000	3000	60*30*31	7500	87	93
JG-4000	4000	68*30*41	10000	113	121
JG-5000	5000	73*40*48	12500	198	213

Material Thickness				Load Capacity Ration				
	mm	inch	JG-3000	JG-2000	JG-1000	JG-600	JG-400	JG-100
T1	up60	up2.36	100%	100%	100%	100%	100%	100%
T2	55	2.16	95%					
T3	50	1.97	90%	95%				
T4	45	1.77	85%	90%				
T5	40	1.57	80%	85%				
T6	35	1.38	70%	75%	90%			
T7	30	1.18	60%	65%	80%			
T8	25	0.98	50%	55%	70%	90%		
T9	20	0.79	40%	45%	60%	75%	90%	
T10	15	0.59	30%	35%	50%	60%	70%	
T11	10	0.39	20%	25%	35%	45%	50%	70%
T12	5	0.20	10%	15%	20%	25%	30%	40%

JG2 Automatic Permanent Magnetic Lifter

Model	Rated Lifting Capacity (KG)	Shape Size (mm)						Test Max Pull Off Force (kg)			Weight (kg)
		A	B	C	D	E	F	G	H		
JG2-1B	1000	685	238	770	410	28	48	102	415	4000	200
JG2-1H	1000	596	285	685	450	28	48	104	410	4000	175
JG2-1.5	1500	760	285	845	450	28	48	104	440	5500	245
JG2-2B	2000	760	328	845	500	28	48	112	440	7000	285
JG2-2H	2000	675	360	758	540	28	48	112	420	7000	265
JG2-3B	3000	862	406	948	585	36	58	112	480	10500	380
JG2-3H	3000	786	358	872	545	36	58	124	480	10500	360
JG2-5B	5000	1016	424	1100	610	38	62	124	580	1500	490
JG2-5H	5000	Developing									
JG2-10	10000										
JG2-20	20000										

