

4-inch Thermal Bar code Label Printer

(M/N:OCBP-402DT)



Features:

More economics:

Built-in dual sensors ensure no paper waste when loading paper.

Easy to operate:

DHCP function make the printer plug-and-play, No more complicated IP address settings.

More durable:

10W big motor and big gear, make the service life longer.

High-end materials:

Japanese ROHM Printer head, the printing life is up to 50km

Smarter editing software:

IOS+Android+Harmony OS +Windows+MAC, five-terminal interoperable free editing software

Product specifications are subject to change without prior notice.

Together We Quest For The Best

Specification

General	
Model	OCBP-402DT
Material	Plastic housing
Optional interface	USB,USB+Bluetooth,USB+Bluetooth +WIFI, USB+LAN
Processor	32 bit CPU
Memory	4MB Flash Memory,320KB RAM
Printer Head life	50Km
Power supply	Input: AC 100V-240V,50-60Hz,Output: DC 24V/2.5A
Accessories	Power adapter,Power cable,USB cable,Manual, outside bracket for option
Sensors	Label edge detection, Out of paper detection, Gap detection, Black mark detection,Cover-open detection
Gap height	2mm Min
Black-mark height	2mm Min
Font and bar-code rotation	0°,90°,180°,270°
Compatible command	TSPL
Printing capability	
Printing method	Direct Thermal
Resolution	203 DPI
Printing speed	152mm /s Max
Printing width	30-108mm
Printing length	10-250mm
Bar-code and character	
Bar-code	1D bar code: Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Coda bar, Interleaved 2 of 5, EAN-8,EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST 2D bar code:PDF417, Maxi code, Data Matrix, QR code
Font	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software
Media	
Paper type	Folded paper or roll paper, die-cut label, black mark paper
Paper width	30-118mm
Media thickness	0.06 ~ 0.22mm
Physical	
Dimension	220*112*102mm

Product specifications are subject to change without prior notice.

OCOM Technologies LimitedWebsite: www.ocominc.com, www.possolution.com.cnE-mail: ocom@ocominc.com

Tel/Fax: +86.755.8605.3207



Weight	Net: 1.02kg
Package box	248*140*170mm/1.87Kg
8 in 1 carton	516*300*360mm /12.4kg
Environment	
Working temperature& humidity	0 to 45 degrees centigrade, 10%~80% No condensation
Storage temperature& humidity	-20 to 60 degrees centigrade , 10%~90% No condensation

Product specifications are subject to change without prior notice.

Together We Quest For The Best