

Warranty	2 year
Panel	
Size	24"
Resolution	1920×1200
Color Depth	True 10bits
Backlight	RGB LED
Viewing Angle	178°×178°
Brightness	250cd/m ²
Contrast Ratio	1000:1
Input Terminals	
Video (Composite)	BNC (×1), 1Vp-p+/-3dB sync negative
3G/HD/SD-SDI	BNC (×2) ,800mVp-p +/-10%
HDMI	HDMI Type-A, compatible with DVI-D
YPbPr (Component)	BNC (×3), can be configured as composite or Y/C
Audio	2 CH Analog stereo, 5dBu, Impedance ≥ 47K, RCA (×2)
Output Terminals	
Composite	BNC (×1), loop through, Automatic termination
3G/HD/SD-SDI	BNC (×2), 800mVp-p +/-10%,Active loop through
Component	BNC (×3), loop through, Automatic termination
Audio Monitor	1 CH Analog stereo, 5dBu, Impedance ≤ 500Ω, RCA (×1)
Earphone	Stereo mini jack (×1)
Speaker	1.0 W +1.0 W
External Control	
GPI	6 GPI Input, RJ45 (×1)
RS485	RS485, can be cascaded, RJ45 (×2)
Ethernet	10/100M Adaptive, RJ45 (×1)
General	
Power	DC 19 V 4.74 A
Power Consumption	45W
Operating Temperature	0°C to 35°C (32°F to 95°F)
	Recommended: 20°C to 30°C (68°F to 86°F)
Operating Humidity	20% to 80% no condensation
Dimensions (W x H x D) (with stand)	569.9 x 418.1 x 210 mm
	22.43 x 16.46 x 8.26 inch
Dimensions (W x H x D) (without stand)	569.9 x380.7 x 97.4 mm
	22.43 x 14.98 x 3.83 inch
Weight (with stand)	10.8 kg (23.8lbs)
Weight (without stand)	9.5 kg (20.9lbs)