

Order Codes	Capacity	W*D*H(mm)
T-NC02 6618	18U	600*600*985
T-NC02 6818	18U	600*800*985
T-NC02 6018	18U	600*1000*985
T-NC02 6622	22	600*600*1162
T-NC02 6822	22	600*800*1162
T-NC02 6022	22	600*1000*1162
T-NC02 6627	27	600*600*1385
T-NC02 6827	27	600*800*1385
T-NC02 6027	27	600*1000*1385
T-NC02 6632	32	600*600*1606
T-NC02 6832	32	600*800*1606
T-NC02 6032	32	600*1000*1606
T-NC02 6637	37	600*600*1829
T-NC02 6837	37	600*800*1829
T-NC02 6037	37	600*1000*1829
T-NC02 6642	42	600*600*2051
T-NC02 6842	42	600*800*2051
T-NC02 6042	42	600*1000*2051

Brand:	TUXIN	Column spacing:	465mm (19 inch)
No:	T-NC02 6642	Material:	SPCC cold rolled steel
Size:	600mm*600mm*42U	Function:	Can install server equipment、the router、 patch panel、 KVM、 UPS、 Network device,etc.
IOS test:	Pass ISO9001:2008 Quality System	Thickness:	Mounting Profile: 2.0mm,others: 1.2mm
Surface treatment:	Degreasing,pickling,phosphating,power coating,etc.	Configuration:	Cage nuts and M6 screws: 40 sets.
Standard:	Comply with ANSI/EIA RS-310-D、 IEC297-2、 DIN41491; PARTI、 DIN41494; PART7、 GB/T3047.2-92 standard; compatible with ETSI	Device Installation:	It is recommended to install network equipment/server device within 350 mm depth.