



Internet Of Things Handheld Terminal HCC-T80S

Features

- 4.5-inch HD screen
- High speed Quad - core
- Android 9.0 system
- 4G full Netcom

Specifications

Performance	
CPU	Cortex-A53 Quad-core 64-bit 2.0GHz high-performance processor
RAM+ROM	2GB+16GB
Expand memory	Micro SD(TF) Supports up to 128GB
System	Android 9.0
Data communication	
WLAN	Dual-band 2.4GHz / 5GHz, Supporting IEEE 802 a/b/g/n/ac protocol
WWAN	2G: GSM (850/900/1800/1900MHz)
	3G: WCDMA (850/900/1900/2100MHz)
	4G: FDD:B1/B3/B4/B7/B8/B12/B20
	TDD:B38/B39/B40/B41
Bluetooth	Support Bluetooth 2.1+EDR/3.0+HS/4.1+HS Transmission distance 5-10 meters
GPS	Support GPS, Galileo, Glonass, Beidou
Data collection	
Barcode scanning (Optional)	
1D Linear scanner	Mindeo SE966 Honeywell N4313
1D Symbologies	Code128,EAN-13,EAN-8,Code39,UPC-A,UPC-E,Codabar,Interleaved 2 of 5,China post 25,ISBN/ISSN,Code93,UCC/EAN-128, GS1 Databar, HIBC, etc.
2D Imager scanner	Newland EM3090 Honeywell N3603 Honeywell N6603
2D Symbologies	PDF417, Micro PDF417, GS1 Composite, Aztec Code, Data Matrix, QR Code, Micro QR Code, MaxiCode, Hanxin Code, etc.

Camera	
Rear camera	8MP HD camera,Support auto focus, Flash, Anti-shake, Macro shooting
NFC (Optional)	
Frequency	13.56MHz
Protocol	Support ISO14443A/B, 15693 agreement
Distance	2cm-5cm
Physical parameter	
Dimensions	166mm×77.5mm×22mm
Weight	< 500g
Display	4.5 inch IPS color display with resolution 480*854
TP	Corning Gorilla glass, supports multi-touch Supported gloves and we thands
Battery capacity	Rechargeable polymer battery (3.8V 4200mAh) removable
	Standby time >350 hours
	Working time > 12 hours
	Charging time <4H, using standard power adapter and data cable
Expansion Card slot	PSAM x 2, Micro SIM card x 1 , TF card × 1
Communication interface	Type-C USB x 1, OTG,POGO Pin x 1
Audio	Speaker (mono), Microphone, Earpiece
Keypad	Support touch screen soft keypad and physical keypad
Sensor	Gravity Sensor,Vibration motor
Language/input method	
Input	English, Pinyin, Five strokes, Handwriting input, Support soft keypad
Language	Language packs in Simplified Chinese, Traditional Chinese, English, Korean, Japanese, Malaysian, etc.
User environment	
Operating temperature	-20℃ - 55℃
Storage temperature	-40℃ - 70℃
Environment humidity	5%RH--95%RH(no condensation)
Drop specification	6 sides Supports 1.5 meters drops and 30 times to the concrete within the operating temperature
Rolling test	500×0.5m rolling for 6 sides

Protection level	IP66
Accessories	
Standard	Adapter, Data cable, Protective film, Instruction manual

Picture

