

	
Model:	VRT-C166-H-4G (5.5" Alarm light PTZ camera)
APP:	V380 Pro
System structure:	Embedded Linux system, ARM chip structure
Chip:	AK3918E V330
Resolution:	3MP 1920*1596
Sensor Resolution:	CMOSGC1054/MIS2006
Lens:	4MM
View angle:	80°
Pan-tilt:	Rotates Horizontal:355° Vertical: 90°
Preset point quantity:	6
Video compression standard:	H.265/20FPS
Minimum illumination:	0.01Lux@ (F2.0, VGC ON), 0.1Lux with IR
Electronic shutter:	Auto
Backlight compensation:	Support
Noise reduction:	2D、3D
LED quantity:	18pcs double core led lights
Network connection:	Support 4G-SIM card and adapt to RJ45 Network port
Night vision	IR-CUT switch Automatic, about 5-8meters (It varies from environment) White Led can be remote control via APP:①Turn ON ②Turn OFF ③ Auto (In automatic mode, the infrared light will be turned ON after the IR-cut switch to night vision auto, it can intelligently detected human body, and Turn ON/OFF the White light intelligently)
Audio:	Built-in microphone and speaker, support two-way audio and real-time transmission. ADPCM audio compression standard, self-adapt to code stream
Network protocol:	TCP/IP、UDP、HTTP、DDNS、DHCP、FTP、NTP
Alarm:	①Motion detection and picture push ②AI Human Tracking
Storage:	TF Card (Max 128G) ; Cloud storage /Cloud disk (optional)
Package Method	30pcs /ctn, Ctn Size:51.4*46*85.5cm Product Size:25.2*15*16.8cm
Power input:	12V/2A adapter
Work environment:	Working temperature:-10℃ ~ + 50℃ Working Humidity: ≤95%RH