



深圳市星光彩科技有限公司
Shenzhen Xing Guang Cai Technology Co., Limited


Add: Building 26, Dingfeng Science Industrial Park, No 2 Xingye 1st Road, Fenghuang village, Fuyong Town baoan district, Shenzhen, China

Contact Person: [Nancy Wu](#) Mob/WhatsApp: [+86 15920053974](#) Wechat: [Sophia-xhy](#)

Email: Nancy@szxgled.com

Web: www.xgled.com <https://szxgled.en.alibaba.com>

P10 Outdoor LED Display Parameter

LED Module		
	pixel pitch	10mm
	module size	320*160mm
	module resolution	32*16dots
	LED	SMD3535
	Scan	1/4scan
	Application	Outdoor
	Weight	0.35KG
	Chip type	Epistar

LED Cabinet		
	Cabinet Size	960mm (W) *960mm (H)
	Cabinet resolution	96*96dots
	module quantity	3*6pcs
	LED driver brand	5V 60A 220V
	Material	Sealed waterproof iron case
	Receiving card	1pcs

LED Screen				
	Pixel	10000dots/m ²	Continuous Working Hours	>72 hours
	Ave power consumption	350W/m ²	Using Life	100,000 hours
	Max power consumption	800W/m ²	MTBF	>10,000H
	Optimum Viewing Distance(m)	≥10m	Scatter OOC Point	<0.01%
	Brightness(cd/m ²)	≥4500cd	Continuous OOC Point	None
	Refresh Rate	960 HZ	IP Grade	IP65
	LED Drive mode	Constant Current	Working Temperature	-35C--- +60C
	Display color	17M——69G	Working Humidity	10---90%



深圳市星光彩科技有限公司 Shenzhen Xing Guang Cai Technology Co., Limited

4. Regular packing:



5. Certifications: CE ROS FCC CCC

