

UC Headset Quotation

No.	Item #	Photo	Specifications	
1	UC-001		Speaker Diameter	Ø30mm
			Speaker Sensitivity	109dB ± 3dB
			Impedance	32Ω
			Frequency Response	20Hz-20000Hz
			Microphone Sensitivity	-38dB ± 3dB
			Microphone Frequency	100-10000Hz
			Cable Length	1.9m ± 5%
			Connector	Type-C + USB dapter
2	UC-001(Black and Silver)		Speaker Diameter	Ø30mm
			Speaker Sensitivity	109dB ± 3dB
			Impedance	32Ω
			Frequency Response	20Hz-20000Hz
			Microphone Sensitivity	-38dB ± 3dB
			Microphone Frequency	100-10000Hz
			Cable Length	1.9m ± 5%
			Connector	Type-C + USB dapter
3	BT-001		Speaker Diameter	Ø30mm
			Speaker Sensitivity	109dB ± 3dB
			Impedance	32Ω
			Operating Frequency	2.402-2.480GHz
			Microphone Sensitivity	-38dB ± 3dB
			Microphone Frequency	100-10000Hz
			Battery Capacity	400mAh
			Working time	> 20H
			Charging time	1.5 hours
4	BT-001(Black and Silver)		Speaker Diameter	Ø30mm
			Speaker Sensitivity	109dB ± 3dB
			Impedance	32Ω
			Operating Frequency	2.402-2.480GHz
			Microphone Sensitivity	-38dB ± 3dB
			Microphone Frequency	100-10000Hz
			Battery Capacity	400mAh
			Working time	> 20H
			Charging time	1.5 hours
5	UC-002		Speaker Diameter	Ø30mm
			Speaker Sensitivity	109dB ± 3dB
			Impedance	32Ω
			Frequency Response	20Hz-20000Hz
			Microphone Sensitivity	-38dB ± 3dB
			Microphone Frequency	100-10000Hz
			Cable Length	1.9m ± 5%
			Connector	Type-C + USB dapter
6	UC-003		Speaker Diameter	Ø40mm
			Speaker Sensitivity	109dB ± 3dB
			Impedance	32Ω
			Frequency Response	20Hz-20000Hz
			Microphone Sensitivity	-38dB ± 3dB
			Microphone Frequency	100-10000Hz
			Cable Length	1.9m ± 5%
			Connector	Type-C + USB dapter
7	UC-004		Speaker Diameter	Ø40mm
			Speaker Sensitivity	109dB ± 3dB
			Impedance	32Ω
			Frequency Response	20Hz-20000Hz
			Microphone Sensitivity	-38dB ± 3dB
			Microphone Frequency	100-10000Hz
			Cable Length	1.9m ± 5%
			Connector	Type-C + USB dapter
8	UC-005		Speaker Diameter	Ø40mm
			Speaker Sensitivity	109dB ± 3dB
			Impedance	32Ω
			Frequency Response	20Hz-20000Hz
			Microphone Sensitivity	-38dB ± 3dB
			Microphone Frequency	100-10000Hz

			<table><tr><td>Battery Capacity</td><td>400mAh</td></tr><tr><td>Working time</td><td>> 20H</td></tr><tr><td>Charging time</td><td>1.5 hours</td></tr><tr><td>Effective Range</td><td>≥10 meters</td></tr></table>	Battery Capacity	400mAh	Working time	> 20H	Charging time	1.5 hours	Effective Range	≥10 meters								
Battery Capacity	400mAh																		
Working time	> 20H																		
Charging time	1.5 hours																		
Effective Range	≥10 meters																		
9	UC-392		<table><tr><td>Speaker Diameter</td><td>Ø40mm</td></tr><tr><td>Speaker Sensitivity</td><td>109dB ± 3dB</td></tr><tr><td>Impedance</td><td>32Ω</td></tr><tr><td>Frequency Response</td><td>20Hz-20000Hz</td></tr><tr><td>Microphone Sensitivity</td><td>-38dB ± 3dB</td></tr><tr><td>Microphone Frequency</td><td>100-10000Hz</td></tr><tr><td>Cable Length</td><td>1.9m ± 5%</td></tr><tr><td>Connector</td><td>Type-C + USB dapter</td></tr></table>	Speaker Diameter	Ø40mm	Speaker Sensitivity	109dB ± 3dB	Impedance	32Ω	Frequency Response	20Hz-20000Hz	Microphone Sensitivity	-38dB ± 3dB	Microphone Frequency	100-10000Hz	Cable Length	1.9m ± 5%	Connector	Type-C + USB dapter
Speaker Diameter	Ø40mm																		
Speaker Sensitivity	109dB ± 3dB																		
Impedance	32Ω																		
Frequency Response	20Hz-20000Hz																		
Microphone Sensitivity	-38dB ± 3dB																		
Microphone Frequency	100-10000Hz																		
Cable Length	1.9m ± 5%																		
Connector	Type-C + USB dapter																		