



M8 male right angle plastic assembly connector, unshielded/M8公头弯头塑胶装配式连接器, 不带屏蔽**Scale drawing/尺寸图****Product photo/产品图****Part number/产品料号**

Pins/针数	Code/型	Part number/产品料号
3pins/3针	A code/A型	8ZU05
4pins/4针	A code/A型	8ZU07

Pin assignment front view/针位分布前视图

A code 3pins A code 4pins
A型3针 A型4针

**General data/常规数据**

Pin numbers/针数	3pins/3针	4pins/4针
Rated voltage/额定电压	60V	30V
Rated current(40°C)/额定电流	3A	3A
Standards/标准	IEC 61076-2-104	
Termination/焊接方式	Screw clamp/螺锁	
Connector locking system/锁紧方式	Screw/螺锁	
Degree of protection/防护等级	IP67, IP68, IP69K	
Wire gauge(mm²)/线规(平方数)	0.14mm²-0.34mm²	
Wire gauge(AWG)/线号(平方数)	26AWG-22AWG	
Suitable cable outer diameter/适合线材外径	3.5mm-5.0mm	
Mechanical operation/插拔次数	>100 mating cycles/大于100次	
Ambient temperature(operation)/操作温度	-25°C~+85°C	
Contact resistance/接触电阻	≤5mΩ	
Insulation resistance/绝缘电阻	≥100MΩ	
Connector body/胶芯	TPU	
Pin/端子	Brass with gold plated/黄铜镀金	
Screw/螺丝	Brass with nickel plated/黄铜镀镍	
Gasket/胶圈	Fluorine ring/氟胶圈	
Customs tariff number/海关编码	8538900000	
Environmental compliance/环境符合标准	RoHS, Reach	