

Brand	Innolux	Model P/N	N140HCN-G53
Diagonal Size	14.0"	Panel Type	a-Si TFT-LCD, LCM
Resolution	1920(RGB)×1080, FHD 157PPI	Pixel Format	RGB Vertical Stripe
Active Area	309.31(W)×173.99(H) mm	Bezel Opening	-
Outline Dim.	315.81(H)×186.09(V) ×5.25(D) mm	Treatment	Antiglare, Hard coating (3H)
Luminance	300 cd/m ² (Typ.)	Contrast Ratio	1000:1 (Typ.) (TM)
View Direction	Symmetry	Response Time	14/11 (Typ.)(Tr/Td)
Viewing Angle	89/89/89/89 (Typ.)(CR≥10) ?	Operating Mode	AAS, Normally Black, Transmissive
Support Color	262K 100% sRGB	Light Source	WLED [10S5P] , 15K hours , With LED Driver
Form Style	Slim (PCBA Bent, T≤3.0mm)	Designed For	
Frame Rate	60Hz ?	Touch Panel	On-Cell Touch, I ² C
Interface Type	eDP (2 Lanes) , eDP1.3 , 40 pins Connector		
Power Supply	3.3V (Typ.)		
Environment	Operating Temperature: 0 ~ 50 °C ; Storage Temperature: -20 ~ 60 °C		

[★ Add to Favorites](#)
[🔊 Book Stock Alert](#)
[+ Add to Compare](#)
[🇺🇸 North American Sales](#)
[🇯🇵 日本販売](#)