Brand	Innolux	Model P/N	N140HCA-EAC Rev.C1
Diagonal Size	14.0"	Panel Type	a-Si TFT-LCD, LCM
Resolution	1920(RGB)×1080, FHD 157PPI	Pixel Format	RGB Vertical Stripe
Active Area	309.31(W)×173.99(H) mm	Bezel Opening	-
Outline(mm)	315.81 × 205.12 × 3 (H×V×D)	Treatment	Antiglare, Hard coating (3H)
Luminance	250 cd/m² (Typ.)	Contrast Ratio	800 : 1 (Typ.) (TM)
Viewing Angle	89/89/89/89 (Typ.)(CR≥10)	Response	14/11 (Typ.)(Tr/Td) ms
Good View at	Symmetry	Work Mode	AAS, Normally Black, Transmissive
Color Depth	262K 45% NTSC	Backlight	WLED , 15K hours , With LED Driver
Outline Shape	Slim (PCBA Flat, T≤3.2mm)	Used for	
Refresh Rate	60Hz	Touchscreen	Without
Signal Type	eDP (2 Lanes) , eDP1.2 , 30 pins Connector		
Voltage Supply	3.3V (Typ.)		
Max. Ratings	Storage Temp.: -20 ~ 60 °C Operating Temp.: 0 ~ 50 °C		

Add to Favorites | Book Stock Alert | Add to Compare | North American Sales | 日本販売