



Smart Handheld POS Terminal R330

Specification

Introduction	R330 Smart Handheld POS Terminal
Processor	Snapdragon 425, 1.4GHz, Quad-core, Cortex-A53
Memory	1GB RAM, 8GB Flash, (2+16 optional)
OS	Android 7.1 Nougat
Display	5.0" HD, 1280*720 IPS; G+FF multi-capacitive touch
Key PAD	Power on / off, Volume up / Scanner
Card Slot Support	PSAM: 1* SAM Card (ISO 7816 standard) SIM: 1*SIM Card (1.8v / 3.0 v)
Fiscal Module	Support 12C or UART interface 30.0±0.2*30.0±0.2*9.2±0.2 mm
Data Connect	Communication: GSM, WCDMA, TDD_LTE, FDD_LTE
	NFC: ISO/ICE 14443 Type A & B, Mifare card at optional
	WIFI: 2.4G/5GHz、Support IEEE802.11a/b/g/n
	Bluetooth: Support 2.1/3.0/4.0, BLE, ibeacon
GPS	Built-in GPS, support A-GPS
Thermal Printer	High-speed 58mm line, 40 mm Roll, low noise, power saving
Camera	Rear Camera: 5.0 M, AF (automatic focus)
	Front Camera(Optional): 0.3 M 3P, FF (Fixed-focus)
Barcode Scanner	Built-in 1D barcode scanning modules
Battery	Two 18650 cell from samsung (ICR 18650-26J) 7.4v / 2600 mAh
Speaker	0.8 W / 85 dB
Earphone-jack	3.5mm standard, support external RFID reader via this connector
Interface	1*Micro USB connector, support OTG USB to RJ45 network
Adaptor	Input: AC 100~240v, 0.5 A, output: 5v / 2 A
Dimensions	198*79*48 (L*W*H) mm
Anti-Drop	1.2 meter

Environment

Normal Operating Temperature: 0-40℃
Storage Temperature: -20℃ ---60℃

Picture

