



Category

SWITCH

- MICRO/DETECTOR SW

- ROCKER SW

- PUSH SW

- TOGGLE SW

- ANTI-VANDAL SW

- CAPACITANCE SW

- SLIDE SW

- PRESSURE SW

- ROTARY SW

- DIP SW

- TACT SW

- LIGHTED TACT SW

- KEYLOCK SW

- SAFETY & CONTROL SW

- VEHICLE SW

SOCKET

WIRE HARNESS

BREAKER



OUR PRODUCT

[Home](#) ▶ [Our Product](#) ▶ [T7 Series](#) ▶ [T7 Series](#)

SWITCH / TOGGLE SW

T7 Series Toggle Switches, 20A 125VAC, 1 to 4 Poles, Locking Lever Available

T7 series toggle switches up to 20A 125VAC, 15A 250VAC
Function: SPST, SPDT, DPST, DPDT, 3PDT, 4PDT

[PDF Download](#)

[Get Information](#)

[Print this page](#)



[ZOOM IN](#)

Feature



- Contacts: Silver alloy

FUSE HOLDER

FUSE

ENCODER

INDICATOR

POTENTIOMETER

CONNECTOR

WATERPROOF CONNECTOR

WATERPROOF PARTS

PCBA

NEW PRODUCT

Products Search



- Bushing: Brass
- Actuator: Brass & Plastic
- Cover: Steel
- Nuts: Steel
- Housing: Phenolic
- Name plate available upon request
- Locking lever optional

Specification

- Rating: 20A 125VAC, 15A 250VAC (cURus)
- Contact Resistance: 20m-ohms max.
- Withstand Voltage: 1500VAC for 1 minute
- Insulation Resistance: 500VDC 200M-ohms min.

How to order

T7	A	1	1	A3	B2	H1	R
RATING	POLE	FUNCTION	ACTUATOR	BUSHING	TERMINAL		
A 15A 125VAC 10A 250VAC	1 -1 POLE 2 -2 POLES 3 -3 POLES	1 ON-OFF 2 ON-ON 3 ON-OFF-ON	A3 - STANDARD 	B1 8.5mm B2 9.5mm B3 11mm B4 12.5mm	H1 - H2 -		
B 20A 125VAC 15A 250VAC	4 -4 POLES	4 (ON)-OFF 5 (ON)-ON 6 (ON)-OFF-ON 7 (ON)-OFF-(ON)	PL - PLASTIC 	B3 11mm	H3 - H4 -		
			PA - LOCKING * FUNCTIONS ONLY: 1 ON OFF 2 ON-ON 3 ON-OFF-ON 	B5 14mm	H5 -		
							ROHS


H1


H2


H3


H4


H5











Item



T7A11PAB5H4R
locked toggle
pulled-to-release

