


General Specification

ID	
Basic information	Model
	Factor
	Dimension
	Weight
Air interface	Technical Standard
	Network frequency
	WIFI
Performance	Maximum Data Throughput
	BB Chipset
	RF chipset
	Flash
	USB charging
	Power
	USIM/SIM
	Battery
	Charging time
	Working time
	Standby time
	LED

	USB
	Antenna
	Buttons
	ESD
Software	UI
	Operating OS
	SW Update
	WIFI Mode
	WIFI Security
	Firewall
	SMS
	Phonebook
	APN Setting
	IPv4 & IPv6
	Data Statistics
	SIM Lock
	Data Lock
Certification	CE/ROHS
Environment	Operating Temperature
	Storage Temperature
	Humidity
Accessory	Color box
	QSG
	Main unit
	Battery
	USB Cable



L816A
Mobile WIFI Hotspot
98*66*15mm
about 85g (with Battery)/45g (No Battery)
Compatible with WCDMA, FDD-LTE, TDD-LTE 802.11 b/g/n
LTE FDD B1/3/5/7/8/20/28, TDD B38/40/41, 3G: B1/3/5/8 Modules can be changed to cover more global
2.4G, 802.11b/g/n 150Mbps
LTE CAT 4
FDD-LTE 150Mbps DL /50Mbps UL
UMTS: Up to 21 Mbps DL and 5.76 Mbps UL (DC- HSPA+ mode)
ASR1803S
ASR5803W
16MB
above 5V/1A
<5W
Micro SIM Card slot
Li-ion Battery 2100mAh
<3.5 hours
5 hours (depend on network)
>20 hrs
1) Power/Battery Status Indicator
2) 4G/3G Network Status Indicator
3) Wi-Fi Indicator

USB 2.0, Charging & Internet
Built-in
POWER, Reset(Pinhole)
ESD Protection circuit; Contact±4KV, Air±8KV
Web-UI
Upto WIN11, MAC OS, Android
Local Update/FOTA
AP
OPEN & WPA2-PSK & WPA-PSK/WPA2-PSK
Mac/IP address filter
Support
Support
Support
Support
Support
Support
support
Normal: -10°C to +55°C
-20° C to +70° C
5%~ 95%