

SWITCHING POWER ADAPTER

It is ideal for all different kinds of digital camera which require DC voltage
3.0/4.5/5.0/6.0/6.5/7.0V for any current under 2500mA

LLAS2500-Plug in Switching Power Adapter

Input: 100-240V AC 50/60Hz

OUTPUT: 3.0/4.5/5.0V DC 2.5A and 6.0/6.5V DC 2.0A and 7V DC 1.9A

CURRENT: 0-2500mA

Inplug plug: AT. ET. ST.

Output plug: With 6 detachable plugs

Please refer to page 2 for ordering information on output plugs

Function:

*With short circuit protection

*Automatic thermal cut off

*Automatic overload cut off

Packing: Individual double blister

Model	Pcs.Per Exp.Ctn	N.W (kg)	G.W (kg)	Measurement (cm)	CBM
LLAS2500	40	7	8	50×38.5×29.5	0.0568



LLAS2500



Hangzhou LianLong Electronic Co., LTD.

Add: Kongjiadai, Xiangfu Town, Hangzhou China P.C.: 310015

Tel: 0086-571-88173481; 88174481; 88170931; 88174978; Fax: 0086-571-88172561

www.Lianlong.com.cn / www.Globalsources.com/lianlong.co E-mail: lianlong@mail.hz.zj.cn