

4 Inch Barcode Printer HCC-K38

Specification

Printing	
Printing Method	Thermal Line
Resolution	203 dpi; Optional 300 dpi
Print Instruction	Tspl (Customizable Cpcl / Zpl / Ep)
Print Width	104 mm
Printing Speed	127 mm/s; Optional 150 mm/s
Print Head Life	50 Km (Label Paper); 150 km (Continuous Paper)
Operating Platform	USB Version: Windows / Linux / Mac OS Bluetooth Version: Windows / Android / IOS
RAM Memory	2 Mb
ROM Flash	2 Mb (USB Version); 4 Mb (Bluetooth Version)
Connection Method	USB / USB + Bluetooth (Wifi Can Be Customized)
Opening Method	Side Button Toggle
Heating Head Temperature Detection	Thermistor
Printing Paper	
Paper Type	Label Paper, Continuous Paper, Black Label Paper, Stacked Paper
Paper Loading Method	Easy Paper Loading / Automatic Feeding
Paper Width	38 - 120 mm
Label Height	Minimum 30 mm; Maximum 250 mm
Label Width	Minimum 38 mm; Maximum 112 mm
Media Thickness	0.06 - 0.18 mm
Paper Cutting Method	Manual Tearing
Axis Detection Method	Mechanical Detection Switch
Out Of Paper Detection	Optocoupler
Print Function	Automatic Paper Recognition, Intelligent Paper Return And Suction, Reprint For Lacking Paper, Defective Pixel Detection And Other Functions
Paper Bin Type	No Built-In Paper Bin (Paper Stand Optional)
Barcode Printing	
Support Language	Support Most Languages, Individual Languages Need To Be Customized
Character	Standard GB18030 Simplified Chinese
Character Size	Ascii Font a: 12 * 24 Ascii Font b: 9 * 17 Chinese Characters: 24 * 24
Extended Character	Cp437, Cp850, Cp852, Cp860, Cp863, Cp865, Cp866,

Table	Wpc1250, Wpc1251, Wpc1252, Wpc1253, Wpc1254
Barcode Type	One-Dimensional Code: Code 39, 39c, i25, Code 93, Itf25, Ean128, Code 128, Codabar, Ean-8, Ean8+2, Ean8+5, Ean-13, Ean13+2, Ean13+5, Upc-a, Upca+2, Upca+5, Upc-e, Upce+2, Upce+5 Msic, Itf14, Ean14, Code11, Post QR Code: Qrcode, Pdf417 (Optional)
Font And Barcode Rotation	Supports
Key Parameters	
Key Operation	Power Button (Black Power Button On The Rear Side) Lid Opening Button (Opening Button On Both Sides) Feed Key (Black Feed Key Above)
Key Operation Function In This Scenario	1. Turn Off, Long Press Feed Key And Power Key : Self-Check Page Printing 2. Standby, Long Press Feed Key For 3 Seconds: Enter The Face-Sheet Learning Mode 3. Open Lid And Press Feed Key For 10 Seconds: Restore Factory Settings 4. Standby, Short Press Feed Key: Automatically Enter a Blank Sheet 5. During Continuous Printing, Short Press Feed Key: Printing Pauses 6. Pause Printing, Short Press Feed Key: Continue Printing
Indicator Status Description	The Indicator Light Keeps On: Normal Standby Indicator Light Flashes: Buzzer Alarm
Buzzer Alarm Prompt	2 Beeps: Printer Head Error 3 Beeps: Lacking Paper 5 Sounds: Overheating Error 6 Sounds: Wrong Opening 7 Sounds: Wrong Stitch Mark
Packing	
USB Interface	1 * Standard USB
Charging Port	DC
Adapter	24V / 2.5A
Accessories	Power Adapter; Power Cord; Usb Data Cable; Quick Safety Guide
Package	Kraft Paper; Pearl Cotton Partition; Pearl Cotton Lining
Product Weight	1 kg
Product Size	222 * 102 * 96 mm
Outer Box Size (Single Unit)	26 * 13.6 * 19.1 cm, 1.71 kg
Outer Box Size (8 Units)	53 * 39.6 * 29 cm, 16 kg

Temperature	Working Temperature: 0-45℃ Storage Temperature: -10-60℃
Humidity	Working Humidity: 20-90% Storage Humidity: 10-90%
Certification	CCC, CE, FCC

Picture

