



PRODUCT DESCRIPTION

- ★Rated temperature:100℃
- ★According to JASO D 608-92
- ★Stranded, tinned or bare copper conductor 0.5--8mm²
- ★Cross linked PVC insulated
- ★Uniform insulation thickness of wire to ensure easy stripping and cutting
- ★Resistant to oil, ozone and abrasion
- ★Internal wiring in automobile where high flexibility thermo and mechanical strength are required

产 品 说 明

- ★ 额定温度： 100℃
- ★ 执行标准:JASO D 608-92
- ★ 导体规格:绞合, 镀锡或裸铜丝
0.5--8mm²
- ★ 交联聚氯乙烯绝缘
- ★ 绝缘厚度均匀
易剥 易裁
- ★ 耐油 耐臭氧 耐磨损
- ★ 用于汽车内部连线, 具高柔软性
高机械强度, 耐高温环境使用

Conductor		Finished product			Maximum Resistance at 20℃
Cross Sectional Area	NO.of Cond	Insulation Thick.	Outside Thick.	Weight	
mm ²	No./mm	mm	mm	kg/km	Ω/mm
0.5F	20/0.18	0.5	2.0	8.52	38.6
0.5	7/0.32	0.5	2.0	8.93	34.6
0.75F	30/0.18	0.5	2.2	11.43	25.8
0.85	11/0.32	0.5	2.2	12.35	22.0
1.25F	50/0.18	0.6	2.7	18.14	15.5
1.25	16/0.32	0.6	2.7	18.25	15.1
2	26/0.32	0.6	3.1	27.06	9.3
3	41/0.32	0.7	3.8	41.84	5.9
5	65/0.32	0.8	4.6	64.32	3.72
8	50/0.45	0.8	5.3	93.07	2.45

Note: The "F" in the table indicates that the conductor is a soft structure